




Color: ■ violet Similar to illustration

Technical data	
Marking method	Thermal transfer
Marking	101 ... 150
Marking (number)	2
Marking direction	Horizontal marking
Marking color	black
Marking type	Numbers
Marking layout	Consecutive numbers per strip
Delivery form	Marker card
Delivery form configuration	10 strips with 10 markers per card
Flammability class per UL94	V2

Physical data	
Marker/strip width	5 ... 5.2 mm
Marker width	5 mm

Mechanical data	
Smear resistance	EN 60998-1:2004



Material data		
Color		violet
UV resistance		EN 60068-2-5:2010 Procedure B
Halogen-free		Yes
Weight		8.8 g
Fire load		0.264 MJ

Commercial data		
PU (SPU)		50 (5) pcs
Packaging type		Box
Country of origin		DE
GTIN		4050821081906
Customs tariff number		49119900000

Product Classification		
UNSPSC		55121731
eCl@ss 10.0		27-14-11-37
eCl@ss 9.0		27-14-11-37
ETIM 9.0		EC000761
ETIM 10.0		EC000761
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 793-5508/000-024	

CAD/CAE-Data

CAE data	
EPLAN Data Portal 793-5508/000-024	

Installation Notes

Application




Separating a strip from the WMB or WMB marker card.



Stretching a WMB marker strip.



Separating an individual marker from the WMB marker strip – for larger terminal blocks.



Snapping a marking strip into the marker slot.

Marking



Snapping a WMB marker strip into the marker slot of the double marker carrier.



Snapping a marking strip into the marker slot.