

# ToLED<sub>o</sub> AVANT T8 CCG L1200 2000LM 865 50K RL

Item No: 0030241


**SYLVANIA**



## Technical Assets

Dimensions (mm)

Photometrics



# ToLEDo AVANT T8 CCG L1200 2000LM 865 50K RL

Item No: 0030241



## General data

Product name	ToLEDo AVANT T8 CCG L1200 2000LM 865 50K RL
Technology	LED
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C...+55°C
ETIM Class	EC001959
E-number FI	4941346
Warranty	5 years

## Optical data

Useful luminous flux ( $\Phi_{use}$ )	2000
Correlated colour temperature (k)	6500
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	170
Photobiological Risk Group	RG0

## Electrical data

Power consumption (W)	13.3
Wattage (W)	13.3
Current (A)	0.08
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.9
Control gear required	No
Inrush Current (A)	10.4
Inrush Duration ( $\mu$ s)	260
Lamp Energy Label (class)	D

## Lifetime data

Lifespan L70 B50	50000
------------------	-------

## Physical data

IP rating	IP20
Nominal Product Length (mm)	1198
Nominal Product Diameter (mm)	28
Weight (kg)	0.172

## Packaging

Product EAN number	5410288302416
Packaging single width (cm)	2.8
Packaging single depth (cm)	2.8
DUN14 (inner)	15410288302413
Packaging outer length / height (cm)	129.6

## Safety data

Optimal operating condition (°C)	-20-55
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Safety message	Suitable for totally enclosed fixture