

P-PIPESTOP16: Stop end for pipe Press Ø16



Commercial information

These fittings offer great advantages with regard to corrosion.

- The body of the fitting consists of brass CW617N.
- The fitting is equipped with a thrust ring to prevent direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- Electrolysis is thus excluded.
- The fitting is equipped with EPDM O-rings and stainless steel press sleeves with 3 control windows.
- To prevent assembly errors, the stainless steel press sleeves are marked with the size and type of press profile that can be pressed.

Basic unit dimensions

Height	34 mm
Length	22 mm
Width	22 mm
Net weight	0.030 kg

Certificates

ATG, DVGW Wasser, ETA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, SABS, EMI, KIWA

Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Outer pipe diameter connection 1	16 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Max. operating pressure at 20 °C	16 Bar
Surface protection connection 1	Untreated	Wrench width	0 Millimetre
Surface treatment connection 1	Untreated	Wrench width union nut	0 Millimetre
System specific	✓	Standard Dimension Ratio (SDR)	0
Nominal diameter connection 1	DN 8		
Connection 1	Press sleeve		
Contour code	TH/BE		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	Brass		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
With drain valve	✗		
With de-aerator	✓		
Capped	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		