

Product Environmental Profile





P3 Switch Disconnector with Flush Mount

Representative	P3-100/EA/SVB-SW (Y7-062603)
product	Product Category: Disconnectors
Description of the product	Eaton's Switch Disconnector are designed to turn off all or part of an installation by disconnecting the installation or part of the installation of all electrical energy or earth, for safety reasons. These switch disconnectors have total 3+N poles, flush mount and with STOP Function.
Homogeneous Environmental Families Covered	The PEP concerns following product offerings from Eaton Moeller® series P3 switch disconnector, P3-100/EA/SVB-SW(Y7-062603) (Reference) as mentioned below: P3-63/EA/SVB-SW (Y7-057857); P3-80/EA/SVB-SW (Y7-400929); P3-63/EA/SVB (Y7-031607); P3-100/EA/SVB (Y7-074320); P3-80/EA/SVB (Y7-400924) *[The product market is spread globally. Different scenarios are studied considering distribution in UK and outside Europe and separate extrapolation factors are given in this PEP considering Europe market as reference]
Functional unit	"Turn off all or part of an installation by separating the installation or part of the installation of all electrical energy or earth, for safety reasons with a rated voltage 690V, and rated current 100A, ensuring isolation characterised by a rated voltage 6000V AC, and with IP Rating of IP65, according to the appropriate use scenario, and during the reference service life of the product of 20 years."
Company information	Eaton Production International GmbH, Claylands Avenue, Dukeries Industrial Estate, United Kingdom. Email: productstewardship-es@eaton.com

Constituent Materials			
Reference product mass	4.75E-01kg (With packaging)		
Category PEP Material	Materials	Mass (kg)	Percentage (%)
Plastics	Polyamide66GF30	1.37E-01	28.7%
Metals	Stainless Steel	9.60E-02	20.2%
Plastics	Polyamide6	7.73E-02	16.3%
Others	Carton	4.78E-02	10.1%
Metals	Brass	4.67E-02	9.8%
Metals	Copper	1.83E-02	3.9%
Plastics	Bakelite	1.33E-02	2.8%
Metals	Steel Wire Rod	8.54E-03	1.8%
Plastics	Polyamide66	6.90E-03	1.5%
Metals	Silver	6.24E-03	1.3%
Plastics	Polybutylene terephthalate	6.00E-03	1.3%
Others	Paper	5.00E-03	1.1%
Plastics	Polycarbonate	4.28E-03	0.9%
Plastics	Ethylene-vinyl acetate	1.21E-03	0.3%
Others	Miscellaneous	1.08E-03	0.2%
	Total	4.75E-01	100.0%

Substance Assessment

The representative product is compliant with the EU-RoHS Directive (2011/65/EU) without any exemption and the product doesn't contain any substance listed as Substance-of-Very-High-Concern (SVHC) on the Candidate List of the EU-REACH Regulation (1907/2006/EC).

Additional Envir	onmental Information
Manufacturing	The reference product is assembled at an Eaton plant in United Kingdom, holding management system
Manufacturing	certifications according to ISO 14001 standards.
Distribution	Eaton is committed to minimizing weight and volume of product and packaging with focus to optimize
Distribution	transport efficiency.
Installation	The installation process does not require any energy consumption and there is no waste other than
mstanation	the obsolete product packaging generated during this step.
Use	Product do not need any maintenance during Use phase.
	The recyclability rate of the overall product is 87% if it is properly dismantled prior to shredding. The
End of life	rate is calculated based on "ECO'DEEE recyclability and recoverability calculation method" (version V1,
	20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

Environmental Impacts

The calculation of the environmental impacts is the result of the Product's Life Cycle Analysis in accordance with ISO 14040/44, covering the entire lifecycle, i.e., "Cradle-to-Grave" including the following life cycle phases: production, distribution, installation, use and end of life.

System modelling was carried out using the commercial LCA software EIME v6.2.1 with database version CODDE-2024-04.

Indicators Set: PEF EF 3.1 (Compliance: PEP ed.4, EN15804+A2) v2.0

	11 2.1 (compliance: 121 ca.1, 2112300 1.712) v2.0
Manufacturing Phase	The product is assembled as well as packed at Eaton Production International GmbH, United Kingdom, plant. Energy model used: United Kingdom
Distribution Phase	Distribution of the product in its packaging from the Eaton's last logistics platform to the installation place in Europe.
Installation Phase	Product is installed in Europe. Treatment of packaging waste is considered in this phase as per country specific statistics given in PSR. Energy model used: Europe
Use Phase	Reference lifetime: 20 Years Usage profile: The product has power loss of 22.5 W at full load condition. For industrial and commercial applications under low voltage scenario considering 50% of the loading rate and 30% use time rate, total losses are 29.5650 kWh over the 20 years. Product do not require any maintenance/replacement during useful life. Energy Model Used: Europe
End of life Phase	Product disposed with WEEE guidelines. Energy model used: Europe
Module-D	Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and loads beyond the boundaries of the system and are not to be included in the life cycle totals.

Environmental Impact Indicators: Mandatory

Mandatory environmental impact indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 - Operational energy use	C1-C4 End of life
Climate change - total (GWP)	kg CO₂ eq.	1.09E+02	4.20E+00	1.13E-01	1.50E-01	1.04E+02	5.82E-01
Climate change - fossil fuels (GWP-f)	kg CO₂ eq.	1.09E+02	4.24E+00	1.13E-01	6.32E-02	1.04E+02	5.73E-01
Climate change - biogenics (GWP-b)	kg CO₂ eq.	2.46E-01	-4.03E-02	0.00E+00	8.64E-02	1.92E-01	8.38E-03
Climate change - land use and land use transformation (GWP-lu)	kg CO₂ eq.	6.88E-06	6.58E-06	0.00E+00	0.00E+00	0.00E+00	3.01E-07
Ozone depletion (ODP)	kg eq. CFC- 11	1.03E-06	5.14E-07	1.74E-10	1.90E-09	5.05E-07	1.19E-08

D - Benefits and loads beyond the system boundaries -2.32E+00 -2.37E+00 -5.19E-02 -5.44E-06

Mandatory environmental impact indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 - Operational energy use	C1-C4 End of life
Acidification (AP)	mole of H ⁺ eq.	5.76E-01	3.77E-02	7.18E-04	2.05E-04	5.34E-01	3.45E-03
Freshwater eutrophication (EP-fw)	kg P eq.	9.85E-04	3.27E-04	4.25E-08	7.33E-07	2.74E-04	3.83E-04
Marine aquatic eutrophication (EP-m)	kg of N eq.	7.05E-02	4.56E-03	3.37E-04	8.30E-05	6.50E-02	4.93E-04
Terrestrial eutrophication (EP-t)	mole of N eq.	1.10E+00	4.33E-02	3.69E-03	5.70E-04	1.04E+00	5.95E-03
Photochemical ozone formation (POCP)	kg of NMVOC eq.	2.21E-01	1.35E-02	9.31E-04	1.37E-04	2.05E-01	1.67E-03
Depletion of abiotic resources - elements (ADP- e)	kg eq. Sb	8.92E-03	8.87E-03	4.46E-09	4.33E-09	3.69E-05	1.20E-05
Depletion of abiotic resources - fossil fuels (ADP-f)	MJ	2.74E+03	8.32E+01	1.58E+00	5.98E-01	2.63E+03	2.49E+01
Water scarcity (WDP)	m³ eq. deprivation worldwide	1.03E+01	1.95E+00	4.30E-04	1.30E-02	7.98E+00	3.44E-01

D - Benefits and loads beyond the system boundaries
-1.90E-02
-3.70E-05
-2.48E-03
-1.92E-02
-6.34E-03
-4.45E-03
-3.98E+01
-1.15E+00

Inventory Flow Indicators: Mandatory

Inventory flow indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 - Operational energy use	C1-C4 End of life
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	MJ	7.02E+02	4.94E+00	2.11E-03	2.00E-01	6.96E+02	6.85E-01
Use of renewable primary energy resources used as raw materials	MJ	1.84E+00	1.84E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	7.04E+02	6.78E+00	2.11E-03	2.00E-01	6.96E+02	6.85E-01
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	MJ	2.73E+03	7.59E+01	1.58E+00	5.98E-01	2.63E+03	2.49E+01
Use of non-renewable primary energy resources used as raw materials	MJ	7.30E+00	7.30E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	2.74E+03	8.32E+01	1.58E+00	5.98E-01	2.63E+03	2.49E+01
Use of secondary materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	m³	2.42E-01	4.57E-02	1.00E-05	5.47E-04	1.88E-01	8.02E-03
Hazardous waste disposed of	kg	4.29E+01	3.79E+01	0.00E+00	3.20E-03	4.57E+00	4.27E-01

beyond the system boundaries
-7.60E-01
-7.71E-01
-1.53E+00
-3.45E+01
-5.33E+00
-3.98E+01
0.00E+00
0.00E+00
0.00E+00
-2.67E-02
-2.00E+01

Inventory flow indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 - Operational energy use	C1-C4 End of life
Non-hazardous waste disposed of	kg	1.88E+01	1.04E+00	3.98E-03	2.09E-02	1.76E+01	1.51E-01
Radioactive waste disposed of	kg	4.50E-03	3.98E-04	2.83E-06	3.45E-06	4.04E-03	5.94E-05
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	5.99E-01	1.84E-01	0.00E+00	4.37E-02	0.00E+00	3.71E-01
Materials for energy recovery	kg	8.28E-03	4.61E-05	0.00E+00	4.94E-03	0.00E+00	3.29E-03
Exported energy	MJ by energy vector	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the product	kg of C.	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the associated packaging	kg of C.	4.40E-02	4.40E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00

D - Benefits
and loads
beyond the
system
boundaries
-3.08E-01
-1.79E-04
0.00E+00

Environmental Impact Indicators: Optional

Optional Environmental impact indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	B6 - Operational energy use	C1-C4 End of life
Emission of fine particles	incidence of diseases	4.73E-06	4.05E-07	5.84E-09	1.19E-09	4.30E-06	2.33E-08
Ionizing radiation, human health	kBq U ²³⁵ eq.	1.78E+02	2.29E+01	2.76E-04	4.99E+00	1.50E+02	1.77E-01
Ecotoxicity, fresh water	CTUe	2.47E+03	2.27E+03	7.43E-02	8.27E-01	1.97E+02	4.63E+00
Human toxicity, cancer effects	CTUh	2.39E-06	2.37E-06	1.99E-12	5.74E-09	1.31E-08	4.02E-10
Human toxicity, non-cancer effects	CTUh	8.14E-07	4.70E-07	3.85E-11	1.82E-10	3.13E-07	3.02E-08
Impacts related to land use/soil quality	-	4.48E+00	6.81E-01	0.00E+00	1.61E-04	2.88E+00	9.17E-01
Total use of primary energy during the life cycle	MJ	3.44E+03	9.00E+01	1.58E+00	7.98E-01	3.33E+03	2.56E+01

D - Benefits
and loads
beyond the
system
boundaries
-2.14E-07
-1.20E+01
-1.95E+03
-1.29E-06
-2.38E-07
-1.52E-02
-4.13E+01

To evaluate the environmental impact of other product covered by this PEP, multiply the impact figures by-Multiplying Factors for Manufacturing, distribution, installation, End of Life and Module-D phase Phase for Europe:

Part No.	Description	Extrapolation Factors for Manufacturing, distribution, installation, End of Life and Module-D phase
Y7-62603 (Reference)	P3-100/EA/SVB-SW	1.00
Y7-57857	P3-63/EA/SVB-SW	1.00
Y7-400929	P3-80/EA/SVB-SW	1.00
Y7-31607	P3-63/EA/SVB	1.00
Y7-74320	P3-100/EA/SVB	1.00
Y7-400924	P3-80/EA/SVB	1.00

Multiplying Factors for Use Phase for Europe:

Part No.	Description	Extrapolation Factor for Use Phase					
Y7-62603 (Reference)	P3-100/EA/SVB-SW	1.00					
Y7-57857	P3-63/EA/SVB-SW	0.60					
Y7-400929	P3-80/EA/SVB-SW	1.00					
Y7-31607	P3-63/EA/SVB	0.60					
Y7-74320	P3-100/EA/SVB	1.00					
Y7-400924	P3-80/EA/SVB	1.00					

Factors for Manufacturing, Distribution, Installation, End of Life and Module-D phase for different geographical regions

Product	Geographical regions	Phases	GWP	GWP-	GWP- b	GWP- lu	ODP	AP	EP-fw	EP- m	EP-t	POCP	ADP- e	ADP- f	WDP
Europe (Reference)		All Phase							1.00						
		Manufacturing, End of Life		1.00											
Y7-027009	Y7-027009 Kingdom		0.29												
(Reference)		Installation	0.99	0.98	1.00	1.00	1.00	0.97	1.00	0.99	1.01	0.98	0.93	0.96	0.99
		Manufacturing							1						
	Outside	Distribution	1.34	1.34	1.00	1.00	1.14	7.00	1.23	3.56	3.55	3.63	1.22	1.22	1.17
	Europe	Installation	0.68	0.30	0.96	1.00	0.35	0.56	0.02	0.34	0.65	0.58	0.31	0.58	0.06
		End of Life	0.34	0.34	0.09	0.001	1.93	0.46	0.001	0.80	0.87	0.66	0.001	0.12	0.06

Factors for use phase for different geographical regions

Product	Geographical regions	ADP- e (kg SB eq.)	ADP- -f (MJ)	AP (mol H ⁺ eq.)	Ep-f (kg P eq.)	Ep-m (kg N eq.)	Ep-t (mol N eq.)	GWP (kg CO₂ eq.)	GWP- b (kg CO ₂ eq.)	GWP- f (kg CO ₂ eq.)	GWP- lu (kg CO ₂ eq.)	ODP (kg CFC- 11 eq.)	POCP (kg NMVOC eq.)	WDP (m³ eq.)
	Europe (Reference)							1.0	0					
	Germany	1.09	0.86	1.50	0.54	1.34	1.39	1.07	0.73	1.07	1.00	1.43	1.35	1.28
	UK	0.79	0.75	0.67	0.79	0.69	1.17	0.71	1.19	0.71	1.00	0.82	0.61	0.66
Y7-062603	Austria	1.65	0.23	0.43	0.01	0.40	0.63	0.37	0.65	0.37	1.00	0.37	0.36	1.10
(Reference)	Netherlands	0.79	0.77	0.80	0.18	0.95	0.98	1.14	1.33	1.14	1.00	1.01	0.94	0.92
	India	0.60	2.47	5.87	0.16	5.13	3.64	3.93	0.25	3.94	1.00	4.74	5.44	2.69
	Czech Republic	0.45	1.66	2.35	1.77	2.05	1.77	1.59	0.44	1.59	1.00	2.02	2.12	1.20
	Finland	0.73	0.86	0.91	1.59	0.68	1.42	0.39	0.61	0.39	1.00	0.71	0.56	0.54
	Denmark	0.83	0.35	1.16	0.04	0.98	1.66	0.56	0.90	0.56	1.00	1.30	0.86	0.58

Disclaimer

This Product Environmental Profile and its content is based on information available to us. It refers to the product at the date of issue. We make no express or implied representations or warranties with respect to the information contained herein.

		-							
Registration Number	EATO-00167-V01.01-EN	EATO-00167-V01.01-EN Drafting rules							
Verifier accreditation Number	VH53	Supplemented by	PSR-0005-ed3.1-EN-2023 08 12						
Date of issue	07-2024	Information and reference documents	www.pep-ecopassport.org						
		Validity period							
Independent verification	Independent verification of the declaration and data, in compliance with ISO 14025: 20								
Internal	ternal X External								
The PCR review was cond									
(DDemain)									
PEPs are compliant with	PEP								
The components of the p	PASS								
other program.	PORT								
Document complies with	FORTS								
Type III environmental de									