

ToLEDo NEOS T8 CCG and AC

ToLEDo NEOS T8 CCG L1500 2300LM 840 30K RL

0030234



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps
- Omni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes
- Lumen output - 2300lm
- High lumen efficacy - 135 lm/W
- Switching cycles - 200,000X
- Average rated life 30,000 hours
- Lamp length - 1500mm
- Wide beam angle
- Suitable for general illumination in offices, supermarkets, department stores, parking lots
- Suitable for operation with electromagnetic gears/CCG and direct mains operation (220-240V)
- 3-Year warranty



PRODUCT OVERVIEW


| | |
|-----------------------------------|---|
| Product name | ToLEDo NEOS T8 CCG L1500 2300LM 840 30K RL |
| Technology | LED |
| Lamp shape | Tube, double-ended |
| Cap/Base | G13 |
| Lamp finish | Frosted/Coated |
| General application | Education, Logistics & Industry, Office, Residential & Consumer |
| ETIM Class | EC001959 |
| E-number FI | 4941339 |
| Warranty | 3 years |
| Useful luminous flux (Fuse) | 2300 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 170 |
| Photobiological Risk Group | RG0 |
| Power consumption (W) | 17 |
| Wattage (W) | 17 |
| Dimmable | No |
| IP rating | IP20 |
| Product EAN number | 5410288302348 |

PHOTOMETRY

ToLEDo NEOS T8 CCG and AC

ToLEDo NEOS T8 CCG L1500 2300LM 840 30K RL

0030234



TECHNICAL DRAWINGS

