



### Features


- Recessed mounting frame accessory with trim, made of aluminium, dimensions: 97x1192mm, ceiling cut-out dimensions: 83x1165mm. Finishing colour RAL9011 (black).

### Product Overview

Product name	OTAO LINEAR RECESSED FRAME BK
Technology	LED (3 SDCM)
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002557
E-number FI	4170669
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Electrical protection	Class III
Housing colour	RAL9011
IP rating	OTHER
IK rating	IK03
Product EAN number	5410288408293
Warranty	5 years

## OTAO LINEAR RECESSED FRAME BK 0040829

### Technical drawings



### Data table

#### GENERAL DATA

Product name	OTAO LINEAR RECESSED FRAME BK
Technology	LED (3 SDCM)
Type of accessory	Mounting kit
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Education, Office
Operating temperature range (°C)	5°C...+50°C
ETIM Class	EC002557
E-number FI	4170669
Warranty	5 years

#### OPTICAL DATA

Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable

#### ELECTRICAL DATA

Electrical protection	Class III
Control gear required	No

#### PHYSICAL DATA

## OTAO LINEAR RECESSED FRAME BK 0040829

Housing colour	RAL9011
IP rating	OTHER
IK rating	IK03
Diffuser finish	Other
Weight (kg)	1.7

### PACKAGING

Product EAN number	5410288408293
Packaging single length / height (cm)	122.0
Packaging single width (cm)	6.1
Packaging single depth (cm)	7.8
DUN14 (inner)	15410288408290
Units per outer package	4
Packaging outer length / height (cm)	124.0
Packaging outer width (cm)	14.2
Packaging outer depth (cm)	19.4

### SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	5-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No