


SK-PIESTOP26: Stop end for pipe Ø26



Commercial information

Non-reusable end cap for Henco pipe. Push-fit fitting

Basic unit dimensions

Height	40 mm
Length	41 mm
Width	40 mm
Net weight	0.044 kg

Certificates

QB (CSTBat), ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Outer pipe diameter connection 1	26 Millimetre
Surface protection connection 1	Untreated	Max. operating pressure at 20 °C	10 Bar
Surface treatment connection 1	Untreated	Wrench width	0 Millimetre
System specific	✓	Wrench width union nut	0 Millimetre
Nominal diameter connection 1	DN 20	Standard Dimension Ratio (SDR)	0
Connection 1	Insert (push-fitting)		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	White		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
With drain valve	✗		
With de-aerator	✗		
Capped	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		