

Smart single switch, screw fixing

410-00110


4 year warranty

Mechanism for smart single switch, with screw fixing. A finishing set and faceplate in the colour of your choice must be ordered separately.

Technical data

Smart single switch, screw fixing.

- Not compatible with the wireless bridge
- LED colour: white
- Maximum MCB rating: 16 A (limited by national installation rules)
- Communication protocol: Easywave
- Maximum radio frequency power: 5 dBm
- Operating frequency: 0.8683 GHz
- Protection degree: IP20
- Flush-mounting frame
 - 1 mm-thick metal
 - galvanized on all sides after cutting, even on the cut edges
 - with 4 grooves with screw hole of 7 mm
 - with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm for mounting on panels
- Required type of flush-mounting box
 - depth: min. 40 mm (cabling space included)
 - claw/screw fixing: 60 mm
 - inner diameter box: 60 mm
 - multiple boxes centre distance horizontal: 71 mm
 - multiple boxes centre distance vertical: 71 mm
 - multiple boxes centre distance vertical: 60 mm for Belgium and France
- Fixing method
 - with screws for simple fixing in a flush-mounting box with grip surfaces
- End border: 4 rectangular openings (7 x 2.5 mm) which, if the flush-mounting box protrudes from the plasterwork, can compensate for a margin of between 1 and 1.2 mm, so that the faceplate can still butt up perfectly against the wall
- Dimensions (HxWxD): 70 x 70 x 42 mm
- Marking: CE



CE

niko

Wiring diagram

