

## Myriad V IP65 White Bezel

MYRIAD IP65 4000K PHASE DIM WHITE  
2049529



### PRODUCT OVERVIEW

Product name	MYRIAD IP65 4000K PHASE DIM WHITE
Technology	LED
Cap/Base	N/A
Mount	Ceiling recessed mounting
Environment	Interior
E-number SE	7462014
Warranty	5 years
Fixture luminous flux (lm)	1050
Luminaire efficacy (lm/W)	105
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG1
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Integral
IP rating	IP65/20
IK rating	IK02
Product EAN number	5025768495290

### DATA TABLE

#### General data

Product name	MYRIAD IP65 4000K PHASE DIM WHITE
Technology	LED
Cap/Base	N/A
Mount	Ceiling recessed mounting
Environment	Interior
E-number SE	7462014

## Myriad V IP65 White Bezel

*MYRIAD IP65 4000K PHASE DIM WHITE*  
2049529

Warranty	5 years
----------	---------

### Optical data

Fixture luminous flux (lm)	1050
Luminaire efficacy (lm/W)	105
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Adjustable chromaticity	N
Photobiological Risk Group	RG1

### Electrical data

Total power consumption (W)	10
Primary Supply/Product voltage - min (V)	220
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Integral
Drive current (mA)	250
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	68500

### Physical data

IP rating	IP65/20
IK rating	IK02
Diffuser material	Glass
Nominal Product Diameter (mm)	76
Weight (kg)	0.39
Recessed Depth (mm)	72

### Packaging

Single packaging type	Carton
Product EAN number	5025768495290
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5
Packaging outer length / height (cm)	17.5

## PHOTOMETRY

