


Insaver U19 IP44 205 620-2050 840 Multi

Item No: 0030551


SYLVANIA

PRO




Technical Assets

Dimensions (mm)



Photometrics

Beam Angle	Beam Diameter (mm)	Beam Area (mm²)	Beam Area (ft²)	Beam Area (in²)
8.5°	6.68	34.21	0.39	5.28
1.6°	1.37	34.21	0.39	5.28
1.1°	0.88	34.21	0.39	5.28
1.0°	0.72	34.21	0.39	5.28
0.5°	0.40	34.21	0.39	5.28
0.3°	0.19	34.21	0.39	5.28



Insaver U19 IP44 205 620-2050 840 Multi

Item No: 0030551

SYLVANIA

General data

Product name	Insaver U19 IP44 205 620-2050 840 Multi
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001744
E-number FI	4278528
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	2050
Fixture luminous flux (lm)	2050
Luminaire efficacy (lm/W)	128
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	70
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	16
Primary Supply/Product voltage - min (V)	220.0
Lamp power factor	0.9
Electrical protection	Class II
Control gear type	LED driver constant current
Dimming method	N/A
Drive current (mA)	500
Inrush Current (A)	10
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	32
Max. products per 16A C Breaker	51
Connectable conductor cross section - Min (mm ²)	0.75
Connectable conductor cross section - Max (mm ²)	1.5

Lifetime data

Lifespan L70 B50	100000
Lifespan L70 B20	100000
Lifespan L70 B10	100000
Lifespan L80 B50	100000
Lifespan L80 B20	88000
Lifespan L80 B10	80000
Lifespan L90 B50	50000
Lifespan L90 B20	43000
Lifespan L90 B10	39000

Insaver U19 IP44 205 620-2050 840 Multi

Item No: 0030551



Physical data

Housing colour	RAL 9010 - Pure white
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Other
Diffuser material	None
Reflector finish	Not Applicable
Nominal Product Height (mm)	60
Nominal Product Diameter (mm)	220
Built-in diameter (mm)	205
Weight (kg)	0.73

Packaging

Product EAN number	5410288305516
Packaging single width (cm)	23.2
Packaging single depth (cm)	8.0
DUN14 (inner)	15410288305513
Packaging outer length / height (cm)	48.0

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-40