

## Ascent 150 II Round White Reflector

ASCENT 150 II 3400 4K DALI WHT  
2059449



### Product features

- The ASCENT 150 II 3400 4K DALI WHT is a high efficient downlight luminaire , Colour rendering index Ra >80, Colour temperature: 4000K Neutral White, Class II, Protection rating IP44/IK03



### PRODUCT OVERVIEW

Product name	ASCENT 150 II 3400 4K DALI WHT
Technology	LED
Cap/Base	Q10S
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Internal
General application	Hospitality, Office, Retail
ETIM Class	EC001744
Warranty	5 years
Useful luminous flux (Fuse)	3400
Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	126
LOR (%)	100
Correlated colour temperature (k)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	80
Glare control	< 27
Photobiological Risk Group	RG0
Total power consumption (W)	27
Electrical protection	Class II
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	DALI, Switch-dim (mains-rated)
Minimum dimming level (%)	1
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP44/20
IK rating	IK03
Product EAN number	5025768594498


## Ascent 150 II Round White Reflector *ASCENT 150 II 3400 4K DALI WHT* 2059449

### PHOTOMETRY

0.5	0.82	E97 ECB	36.5°	1202 1006
1.0	1.65	E97 ECB	36.5°	5922 421
1.5	2.47	E97 ECB	36.5°	183 107
2.0	3.30	E97 ECB	36.5°	485 105
2.5	4.12	E97 FCB	36.5°	301 85
3.0	4.95	E97 ECB	36.5°	302 81

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 79.8°)



### TECHNICAL DRAWINGS

