

SPECIFICATION

Description	220-240V LED Driver, Constant Voltage Driver
Electrical Characteristics	Ta = 25°C, 220-240Vrms input, standard reference load; unless otherwise specified
Class II, IP20, thermally protected 110, independent driver	

Product Name	215-002
---------------------	---------

Input Parameters

Rated Input Voltage	Uin	220-240VAC
Input Current (Full load)	Iin	0.13A
Input Frequency	fin	50/60Hz
Maximum Input Power	Pin	23W
Power Factor (Full load)	λ	≥ 0.80
Efficiency (Full load)	η	$\geq 82\%$
No-load power		≤ 0.5 W
Inrush current		≤ 10.0 A
Turn on time		≤ 500 ms

Output Parameters

Output Voltage	Vout	12V $\pm 5\%$
Output Current (Full load)	Iout	1.5A
Output Power (Full load)	Pout	18W
Operating Frequency(Full load)	Fout	60-70KHz
Ripple & Noise		≤ 300 mV
Load Regulation		$\leq 5\%$
Line Regulation		$\leq 5\%$

Ambient

Storage Temperature	ts	-20 ... + 70°C
Operating Ambient Temperature	ta	-20 ... + 50°C
Case Temperature at tc Point	tc	85°C
Relative humidity		5 ... 85%

Protection

No Load		Auto-recovery if fault is removed
Over Load		Auto-recovery if fault is removed
Short Circuit		Auto-recovery if fault is removed

System Parameters



Hi-pot		3.75KVAC, I leakage < 5.0mA, 60s
Average Service Life		30,000Hours

Compliances and approvals

Safety		EN 61347-2-13
RFI		EN 55015
Harmonics		EN 61000-3-2 Class C
Immunity		EN 61547

Note

- All parameters NOT specially mentioned are measured at 240VAC input, rated load and 25 of ambient temperature.
- Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.
- Expected Life:tc=80°C, 0.2%/1000h failure rate.

Physical Parameter

Dimensions(LxWxH): 115x45x21mm

Housing Material:PC Plastic

Captured Terminal Screw for 0.75~2.5mm²