


VS-0604: Manifold Reducer with O-ring 1"x1/2"



Commercial information

Messing reductiestuk met O-ring voor verdeler

Basic unit dimensions

Height	41 mm
Length	16 mm
Width	41 mm
Net weight	0.079 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material connection 2	Brass	Length	15.5 Millimetre
Reducing	✗	Wrench width union nut	0 Millimetre
Eccentric	✗	Medium temperature (continuous)	-10 70 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	10 Bar
Main colour fitting	Brass	Standard Dimension Ratio (SDR)	0
With buffer stud	✗		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With connection indicator	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		