

# Connector PowerTOP Xtra

Part number: 14513



**MENNEKES**  
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1  
57399 Kirchhundem  
GERMANY

[www.MENNEKES.org](http://www.MENNEKES.org)

## Product Description

- screw connection technology ErgoCONTACT
- economic enclosure design with nubbed grip areas
- enclosure with thread lock and safety slide
- X-CONTACT
- protection against kinking
- strain relief
- rubberised cable gland with sealing
- area for self-adhesive labels

## Technical Details

| Connector PowerTOP Xtra                                             | 14513                           |
|---------------------------------------------------------------------|---------------------------------|
| Product serie                                                       | PowerTOP Xtra                   |
| Ampere                                                              | 32A                             |
| Number of poles                                                     | 3p                              |
| Clock position                                                      | 6h                              |
| Nominal voltage AC                                                  | 230V                            |
| Nominal frequency                                                   | 50 - 60 Hz                      |
| Protection type IP                                                  | IP54                            |
| Contact carrier                                                     | standard                        |
| X-CONTACT                                                           | yes                             |
| Connection                                                          | screw terminals - ErgoCONTACT   |
| Contact screw drive                                                 | PZ2, slot                       |
| Tightening torque connection terminal                               | 1.8 Nm                          |
| Recommended wire end treatment for supply cable connection terminal | ferrule square gasproof crimped |
| Strip length jacket                                                 | 68 mm                           |
| Strip length conductor PH + N                                       | 12 - 15 mm                      |
| Strip length conductor PE                                           | 12 - 15 mm                      |
| Pilot contact                                                       | without pilot contact           |
| Conductor cross-section min.                                        | 2.5 mm <sup>2</sup>             |
| Conductor cross-section max.                                        | 6 mm <sup>2</sup>               |
| Cable kink protection                                               | integrated in cable gland       |

|                             |                            |
|-----------------------------|----------------------------|
| Connector PowerTOP Xtra     | 14513                      |
| Protective grommet          | without protective grommet |
| Militärausführung           | nein                       |
| Weight (net)                | 370 g                      |
| Packaging unit              | 10 pcs                     |
| Quantity per pallet         | 540 pcs                    |
| EAN / identification number | 4015394296751              |

#### Permissible ambient conditions

|                                 | Min.   | Max.  |
|---------------------------------|--------|-------|
| Permissible ambient temperature | -25 °C | 40 °C |

#### Material properties

|              |                                         |
|--------------|-----------------------------------------|
| Cover        | PA6 blue [similar RAL 5007]             |
| Front part   | PA6 blue [similar RAL 5007]             |
| Hinged lid   | PC blue [similar RAL 5007]              |
| Clamp basket | PA6 natural colour [no RAL colour code] |
|              | TPE natural colour [no RAL colour code] |
| Fastening    | PA6 squirrel grey [similar RAL 7000]    |
|              | TPE anthracite [similar RAL 7016]       |

#### Material resistance

The material resistance overview can be found on the website in the section “Knowledge” - “Product knowledge” - “Materials”.


#### Material and environmental properties

|                                   |     |
|-----------------------------------|-----|
| RoHS 2011/65/EU incl. 2015/863/EU | ✓   |
| POP regulation (EU) 2019/1021     | ✓   |
| Halogen-free                      | yes |

#### Regulations and Standards

|                           |                              |
|---------------------------|------------------------------|
| Norm                      | DIN EN IEC 60309-2           |
| Declaration of Conformity | CE                           |
| Test label                | CB Zertifikat, VDE, EAC, CQC |

# Dimensional Drawing



| Drawing<br>3 MB 79                   | Amp.<br>Poles | 16   |       |       | 32   |      |      |
|--------------------------------------|---------------|------|-------|-------|------|------|------|
|                                      |               | 3    | 4     | 5     | 3    | 4    | 5    |
| Dim. in mm                           | a             | 165  | 177   | 174   | 211  | 211  | 209  |
|                                      | b             | 55   | 68    | 69    | 78   | 78   | 80   |
|                                      | h             | 72   | 93    | 98    | 100  | 100  | 108  |
| y min. from                          |               | 7    | 8     | 8     | 10.5 | 10.5 | 13.5 |
| to max. mm                           |               | -13  | -15.5 | -15.5 | -18  | -18  | -20  |
| Terminal for cond. cross             |               | 1    | 1     | 1     | 2.5  | 2.5  | 2.5  |
| section (mm <sup>2</sup> ) min.-max. |               | -2.5 | -2.5  | -2.5  | -6   | -6   | -6   |