

SPECIFICATION

Description	220-240V LED Driver, Constant Voltage Driver
Electrical Characteristics	Ta = 25°C, 220-240Vrms input, standard reference load; unless otherwise specified
Class II, IP20, thermally protected 110, independent driver	

Product Name		215-011
---------------------	--	---------

Input Parameters

Rated Input Voltage	Uin	220-240VAC
Input Current (Full load)	Iin	0.9A
Input Frequency	fin	50/60Hz
Maximum Input Power	Pin	169W
Power Factor (Full load)	λ	≥ 0.95
THD(Full load)		$\leq 15\%$
Efficiency (Full load)	η	$\geq 90\%$
No-load power		$\leq 0.5W$
Inrush current		$\leq 65A$
Turn on time		$\leq 500ms$

Output Parameters

Output Voltage	Vout	12V \pm 5%
Output Current (Full load)	Iout	12.5A
Output Power (Full load)	Pout	150W
Operating Frequency(Full load)	Fout	90~115KHz
Ripple & Noise		$\leq 800mV$
Load Regulation		$\leq 5\%$
Line Regulation		$\leq 5\%$

Ambient

Storage Temperature	ts	-20 ... + 70°C
Operating Ambient Temperature	ta	-20 ... + 50°C
Case Temperature at tc Point	tc	90°C
Relative humidity		5 ... 85%

Protection

No Load		Auto-recovery if fault is removed
Over Load		Auto-recovery if fault is removed
Short Circuit		Auto-recovery if fault is removed

System Parameters

Withstand voltage		3.75KVAC, Ileakage<5.0mA, 60S
Expected Life		30,000Hours

Compliances and approvals

Safety		EN 61347-2-13
RFI		EN 55015
Harmonics		EN 61000-3-2 Class C
Immunity		EN 61547

1. All parameters NOT specially mentioned are measured at 240VAC input, rated load and 25 of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.
3. Expected Life:tc=80°C, 0.2%/1000h failure rate.

Physical Parameter

Dimensions(LxWxH): 210x67x34mm

Housing Material::PC Plastic

Captured Terminal Screw for 0.75~2.5mm²



