Technical data sheet

MS5030 mounting rail, slot 22 mm, FT, perforated

Item number: 1121243



Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.

E30 E90

St Steel

FT Hot-dip galvanised

Master data

Item number	1121243
Type	MS5030P0300FT
Description 1	Profile rail
Description 2	perforated, slot 22mm
Manufacturer	OBO
Dimension	300x50x30
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	85 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,863 kg CO2e / 1 Piece

Technical data sheet

MS5030 mounting rail, slot 22 mm, FT, perforated

Item number: 1121243

Dimensions



Length	300 mm
Width	50 mm
Height	30 mm
Dimension L	300 mm

Technical data

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Drill hole spacing, centre	50 mm
Maintain electrical functions	yes
Material thickness	3 mm
With perforation	yes
With toothing	no
Profile shape	C profile
ROHS-conformant	yes
Slot width	22 mm
Static value A	3.39 cm²
Static value Iy	3.99 cm⁴
Static value Iz	13.11 cm⁴
Static value Wy	3.95 cm³
Static value Wz	6.38 cm³