

Central battery system ZB-S with STAR technology

Components and options

SKU CG-S 1 x 6 A



SKU CG-S 1 x 6 A

Hybrid operation of maintained light, non-maintained light and switched maintained light in a single circuit can be programmed with no additional data cable.

- Up to 20 luminaires can be monitored individually
- Separate fusing for mains and battery operation
- Easy access to fuses
- LED indicates fault and Run/ON for each circuit
- Supplies electronic ballast and LED luminaires
- Service-friendly modular units are wired up and ready to connect to 3-tier 4 mm² disconnect neutral terminals (optional)
- Gear tray mounting

Fusing	10 AT / 6.3 x 32
Continuous current rating	6 A per circuit
Max. inrush current	250 A per circuit
Typical switch over time	AC/DC approx. 450 ms
Own consumption	3.85 W

Ordering details

Type	Scope of supply	Order No.
SKU	Circuit change over module SKU CG-S 1 x 6 A	40071347345
Spare part	Fuse 10 AT (6.3 x 32), PU: 10 pcs.	40071070715

SOU CG-S 2 x 4 A



SOU CG-S 2 x 4 A

Hybrid operation of maintained light, non-maintained light and switched maintained light in a single circuit can be programmed with no additional data cable.

- Up to 20 luminaires can be monitored individually
- AC/DC switching per module
- Separate AV-feed for rental current
- Easy access to fuses
- LED indicates fault and Run/ON for each circuit
- Supplies electronic ballast and LED luminaires
- Service-friendly modular units are wired up and ready to connect to 3-tier 4 mm² disconnect neutral terminals (optional)
- DIN rail mounting

Fusing	8 AT / 6.3 x 32
Continuous current rating	4 A per circuit
Max. inrush current	250 A per circuit
Typical switch over time	AC/DC approx. 450 ms
Own consumption	≤ 9 W (for 2 x 4 A)
Dimensions	178 x 108 x 60

Ordering details

Type	Scope of supply	Order No.
SOU CG-S 2 x 4 A	Switching over unit SOU CG 2 x 4 A	40071360430
Spare part	Fuse 8 AT (6.3 x 32), PU: 10 pcs.	40071360484