






Serie 44 CE - Waterdichte opbouwdozen conform ANSI/UL 50 en gemaakt van hoogwaardige technopolymeren. De serie is inclusief IP56 met gladde wanden, gewone schroef (GWT 960 °C).

Isolatie klasse	II (volgens IEC 61140 normen)	Kleur	Grijs RAL 7035
IP waarde	IP56	Materiaal	Technopolymeer GWPLAST 75
Mechanische weerstand	IK08	Interne afm. LxHxD (mm)	150 x 110 x 70
Max. Ø gaten mogelijk	29 mm	Dekselschroeven (aantal en type)	4 - RVS
Toepassing	Speciaal gebruik	Gloeidraadtest	960 °C
Deksel	Gewoon geschroefd	Bedrijfstemperatuur	-25 +50 °C
Electrocod	02211	Thermodruk met kogel	75 °C
Koppel schroeven aandraaien	1.2 NM	Muren	Glad
Accessoires voor isolatieherstel	GW44622		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL



TECHNICAL SYMBOLOGY



II (volgens IEC 61140 normen)

IP

IP56

IK

IK08

GWT

960 °C

INSTALLATION



STANDARDS/APPROVALS

