



Certificate number: 2309792 (1)

Issued 21/09/2023

Expires 21/09/2028

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Henco Industries NV.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Henco Industries NV
Toekomstlaan 27 B-2200 HERENTALS
Belgium



KUKreg4

Product Certificate

Appendix to Certificate number: 2309792

The following products belong to this certificate

<p>PRODUCT DESCRIPTION Range of 2,3,4 port manifold type VB and VBS. The eurocone connections on the branches are covered by the Henco Schroef type EK compression fittings and Henco Press type 19P/19PK press fittings in combination with Henco Standard and Henco RIXc pipes. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) VB050502-BLAUW MANIFOLD 3/4 WITH BALL VALVES - 2 EK-CONNECTIONS BLUE VB050502-ROOD MANIFOLD 3/4 WITH BALL VALVES - 2 EK-CONNECTIONS RED VB050503-BLAUW MANIFOLD 3/4 WITH BALL VALVES - 3 EK-CONNECTIONS BLUE VB050503-ROOD MANIFOLD 3/4 WITH BALL VALVES - 3 EK-CONNECTIONS RED VB050504-BLAUW MANIFOLD 3/4 WITH BALL VALVES - 4 EK-CONNECTIONS BLUE VB050504-ROOD MANIFOLD 3/4 WITH BALL VALVES - 4 EK-CONNECTIONS RED VB060502-BLAUW MANIFOLD 1 WITH BALL VALVES - 2 EK-CONNECTIONS BLUE VB060502-ROOD MANIFOLD 1 WITH BALL VALVES - 2 EK-CONNECTIONS RED VB060503-BLAUW MANIFOLD 1 WITH BALL VALVES - 3 EK-CONNECTIONS BLUE VB060503-ROOD MANIFOLD 1 WITH BALL VALVES - 3 EK-CONNECTIONS RED VB060504-BLAUW MANIFOLD 1 WITH BALL VALVES - 4 EK-CONNECTIONS BLUE VB060504-ROOD MANIFOLD 1 WITH BALL VALVES - 4 EK-CONNECTIONS RED VBS050502-BL MANIFOLD 3/4 WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT BLUE VBS050502-GR MANIFOLD 3/4 WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT GREEN VBS050502-RO MANIFOLD 3/4 WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT RED VBS050503-BL MANIFOLD 3/4 WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT BLUE VBS050503-GR MANIFOLD 3/4 WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT GREEN VBS050503-RO MANIFOLD 3/4 WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT RED VBS050504-BL MANIFOLD 3/4 WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT BLUE VBS050504-RO MANIFOLD 3/4 WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT RED VBS060502-BL MANIFOLD 1" WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT BLUE VBS060502-RO MANIFOLD 1" WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT RED VBS060503-BL MANIFOLD 1" WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT BLUE VBS060503-RO MANIFOLD 1" WITH VALVE +EK + O-RING CONNECTION/ALIGNMENT RED VBS060504-BL MANIFOLD 1" WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT BLUE VBS060504-RO MANIFOLD 1" WITH VALVE+EK+O-RING CONNECTION/ALIGNMENT RED</p>
<p>SIZE: See model.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 85°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C. For above ground use only.</p>
<p>MARKING HN and size on manifold body.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes