


## Walraven RapidRail® Connector 135° (S/S)

(G3512)

to make Walraven RapidRail® fabrications



### Features & benefits

- connector with pre-assembled Walraven RapidRail® Slide nut(s)
- to make rail fabrications
- suitable for rails 27x18, 30x15, 30x20, 30x30, 30x45, 38x40
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- zinc plated
- For detailed technical information about our RAL marked products, please see the RAL datasheet in our web catalogue.



| Productnumber    | For Rail Type                            | Model | Angle    | Width | Material Thickness | Heart To Heart Distance | Torque Moment For Installation | Maximum Allowed Load Faz | Maximum Allowed Load Fax |
|------------------|------------------------------------------|-------|----------|-------|--------------------|-------------------------|--------------------------------|--------------------------|--------------------------|
| Reference Letter |                                          |       | $\alpha$ | $w$   | $MT$               | $k$                     | $T_{inst}$                     | $F_{a,z}$                | $F_{a,x}$                |
| Unit description |                                          |       | °        | mm    | mm                 | mm                      | Nm                             | N                        | N                        |
| 6584053          | 27x18, 30x15, 30x20, 30x30, 30x45, 38x40 | Angle | 135      | 30    | 3.00               | 0                       | 15                             | 1,336                    | 448                      |