

# Finishing set for 4-pole flush-mounting socket outlet for the public telecommunication network in the Netherlands (PTT), white

101-69010

4 year warranty

Central plate for 4-pole flush-mounting socket outlet for the public telecommunication network in the Netherlands (PTT). The central plate is fixed on a 4-pole flush-mounting socket outlet by means of a screw with mixed screwhead (Pz1 slot 1 x 5.5 mm). This central plate is surrounded with a flat edge that is equipped at all 4 corners with a rectangular opening, each containing a multi-positional snap hook. The construction of the central plate ensures that the faceplate can always be attached flat to the wall, even in cases of untidy plasterwork. Finishing colour: white.



## Technical data

Finishing set for 4-pole flush-mounting socket outlet for the public telecommunication network in the Netherlands (PTT), white. This central plate is surrounded with a flat edge that is equipped at all 4 corners with a rectangular opening, each containing a multi-positional snap hook. The construction of the central plate ensures that the faceplate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The flat edge around the central plate also has 4 round openings that ensure the correct positioning of the faceplate in relation to the central plate. After mounting all components (faceplate, finishing set and switch), no metal parts are visible thanks to the flat edge of the central plate.

- Function: Central plate for 4-pole flush-mounting socket outlet for the public telecommunication network in the Netherlands (PTT). The central plate is fixed on a 4-pole flush-mounting socket outlet by means of a screw with mixed screwhead (Pz1 slit 1x5.5mm).
  - Material central plate: The central plate is made of rigid PC and ASA. The base material is coloured in mass.
  - Colour: white (coloured in mass, approximately NCS S 0502 - Y50R, RAL 9010)
  - Dismantling: To dismount simply unscrew the central plate.
  - Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
  - Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
  - Fire safety
    - The plastic parts of the central plate are self-extinguishing (comply with a filament test of 650°C)
    - The plastic parts of the central plate are halogen-free.
  - Dimensions of finishing with flat edge: 56 x 56 mm (HxW)
- Dimensions of visible area of finishing: 45 x 45 mm (HxW)
- Dimensions (HxWxD): 44.5 x 44.5 x 8.6 mm
  - Marking: CE

CE

[www.niko.eu](http://www.niko.eu)

**niko**

101-69010 - 26-07-2023