


Data Sheet | Item Number: 262-259


4-conductor terminal strip; without push-buttons; with snap-in mounting feet; 9-pole; for plate thickness 0.6 - 1.2 mm; Fixing hole 3.5 mm Ø; 4 mm²; CAGE CLAMP®; 4,00 mm²; gray

<https://www.wago.com/262-259>



Color: ■ gray

Similar to illustration



Dimensions in mm

Electrical data

| Ratings per IEC/EN            |                                                           |
|-------------------------------|-----------------------------------------------------------|
| Nominal voltage (III/3)       | 630 V                                                     |
| Rated impulse voltage (III/3) | 8 kV                                                      |
| Rated current                 | 32 A                                                      |
| Legend (ratings)              | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

| Approvals per |  | UL 1059 |       |       |
|---------------|--|---------|-------|-------|
| Use group     |  | B       | C     | D     |
| Rated voltage |  | 300 V   | 300 V | 300 V |
| Rated current |  | 20 A    | 20 A  | 10 A  |

| Approvals per |  | CSA 22.2 No 158 |       |       |
|---------------|--|-----------------|-------|-------|
| Use group     |  | B               | C     | D     |
| Rated voltage |  | 600 V           | 300 V | 600 V |
| Rated current |  | 5 A             | 25 A  | 5 A   |

Connection data

|                            |    |
|----------------------------|----|
| Connection points          | 36 |
| Total number of potentials | 9  |
| Number of levels           | 1  |

| Connection 1                    |                                    |
|---------------------------------|------------------------------------|
| Connection technology           | CAGE CLAMP®                        |
| Actuation type                  | Operating tool                     |
| Connectable conductor materials | Copper                             |
| Solid conductor                 | 0.08 ... 4 mm² / 28 ... 12 AWG     |
| Fine-stranded conductor         | 0.08 ... 4 mm² / 28 ... 12 AWG     |
| Strip length                    | 9 ... 10 mm / 0.35 ... 0.39 inches |
| Pole number                     | 9                                  |
| Wiring direction                | Side-entry wiring                  |



| Physical data           |                        |
|-------------------------|------------------------|
| Width                   | 111 mm / 4.37 inches   |
| Height from the surface | 23.1 mm / 0.909 inches |
| Depth                   | 33.5 mm / 1.319 inches |
| Module width            | 12 mm / 0.472 inches   |

| Mechanical data |                 |
|-----------------|-----------------|
| Design          | horizontal type |
| Mounting type   | Snap-in foot    |
| Marking level   | Side marking    |

| Material data               |                                                                                                                        |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
| Note (material data)        | <a href="https://www.wago.com/us/material-specifications">Information on material specifications can be found here</a> |
| Color                       | gray                                                                                                                   |
| Material group              | I                                                                                                                      |
| Insulation material         | Polyamide (PA66)                                                                                                       |
| Flammability class per UL94 | V0                                                                                                                     |
| Fire load                   | 1.056 MJ                                                                                                               |
| Halogen-free                | Yes                                                                                                                    |
| Weight                      | 62.9 g                                                                                                                 |

| Commercial data       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-14-11-06   |
| eCl@ss 9.0            | 27-14-11-06   |
| ETIM 8.0              | EC001284      |
| ETIM 7.0              | EC001284      |
| PU (SPU)              | 50 pcs        |
| Packaging type        | Box           |
| Country of origin     | DE            |
| GTIN                  | 4044918641739 |
| Customs tariff number | 85369010000   |

| Environmental Product Compliance |                         |
|----------------------------------|-------------------------|
| RoHS Compliance Status           | Compliant, No Exemption |

Approvals / Certificates

| General approvals                                                            |          |                  | Declarations of conformity and manufacturer's declarations |          |                  |
|------------------------------------------------------------------------------|----------|------------------|------------------------------------------------------------|----------|------------------|
| <div><div>CCA</div><div>KEMA<br/>KEUR</div><div>CSA</div><div>UL</div></div> |          |                  | Approval                                                   | Standard | Certificate Name |
| Approval                                                                     | Standard | Certificate Name | EU-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG    | -        | -                |
| CCA<br>DEKRA Certification B.V.                                              | EN 60998 | NTR-NL 6510      | UK-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG    | -        | -                |
| CCA<br>DEKRA Certification B.V.                                              | EN 60998 | 2110272.03       |                                                            |          |                  |
| CSA<br>DEKRA Certification B.V.                                              | C22.2    | 70010891         |                                                            |          |                  |
| UR<br>Underwriters Laboratories<br>Inc.                                      | UL 1059  | E45172           |                                                            |          |                  |



Approvals for marine applications

|  |  |  |  |
|----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Approval                                                                         | Standard                                                                          | Certificate Name                                                                  |                                                                                   |
| ABS<br>American Bureau of Ship-<br>ping                                          | -                                                                                 | 19-HG1869868-PDA                                                                  |                                                                                   |
| BV<br>Bureau Veritas S.A.                                                        | EN 60947                                                                          | 07436/F0 BV                                                                       |                                                                                   |
| DNV GL<br>Det Norske Veritas, Ger-<br>manischer Lloyd                            | -                                                                                 | TAE00001V2                                                                        |                                                                                   |
| LR<br>Lloyds Register                                                            | IEC 60998                                                                         | LR22173030TA                                                                      |                                                                                   |

Downloads

Environmental Product Compliance

| Compliance Search                           |                                                                                   |
|---------------------------------------------|-----------------------------------------------------------------------------------|
| Environmental Product<br>Compliance 262-259 |  |

Documentation

| Additional Information |                   |                                                                                                     |
|------------------------|-------------------|-----------------------------------------------------------------------------------------------------|
| Technical Section      | pdf<br>2240.62 KB | <a href="#"></a> |

| Bid Text |            |                 |                                                                                                       |
|----------|------------|-----------------|-------------------------------------------------------------------------------------------------------|
| 262-259  | 19.02.2019 | xml<br>3.08 KB  | <a href="#"></a> |
| 262-259  | 17.08.2017 | doc<br>25.50 KB | <a href="#"></a> |

CAD/CAE-Data

| CAD data             |                                                                                     | CAE data                     |                                                                                       |
|----------------------|-------------------------------------------------------------------------------------|------------------------------|---------------------------------------------------------------------------------------|
| 2D/3D Models 262-259 |  | EPLAN Data Portal<br>262-259 |  |
|                      |                                                                                     | WSCAD Universe<br>262-259    |  |
|                      |                                                                                     | ZUKEN Portal 262-259         |  |



1 Compatible Products

1.1 Optional Accessories

1.1.1 DIN-rail

1.1.1.1 Mounting accessories



**Item No.: 210-154**  
Aluminum carrier rail; 1000 mm long; 18 mm wide; 7 mm high; silver-colored

1.1.2 Ferrule

1.1.2.1 Ferrule



**Item No.: 216-301**  
Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; insulated; electro-tin plated; yellow



**Item No.: 216-321**  
Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; insulated; electro-tin plated; yellow



**Item No.: 216-151**  
Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated



**Item No.: 216-131**  
Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated; silver-colored



**Item No.: 216-302**  
Ferrule; Sleeve for 0.34 mm<sup>2</sup> / 22 AWG; insulated; electro-tin plated; light turquoise



**Item No.: 216-322**  
Ferrule; Sleeve for 0.34 mm<sup>2</sup> / 22 AWG; insulated; electro-tin plated; light turquoise



**Item No.: 216-132**  
Ferrule; Sleeve for 0.34 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated



**Item No.: 216-152**  
Ferrule; Sleeve for 0.34 mm<sup>2</sup> / AWG 24; uninsulated; electro-tin plated



**Item No.: 216-241**  
Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; white



**Item No.: 216-201**  
Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; white



**Item No.: 216-221**  
Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; white



**Item No.: 216-141**  
Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; uninsulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 1/08.92



**Item No.: 216-101**  
Ferrule; Sleeve for 0.5 mm<sup>2</sup> / AWG 22; uninsulated; electro-tin plated; silver-colored



**Item No.: 216-121**  
Ferrule; Sleeve for 0.5 mm<sup>2</sup> / AWG 22; uninsulated; electro-tin plated; silver-colored



**Item No.: 216-242**  
Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray



**Item No.: 216-262**  
Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray



**Item No.: 216-202**  
Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; gray



**Item No.: 216-222**  
Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; gray



**Item No.: 216-142**  
Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; uninsulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 1/08.92



**Item No.: 216-102**  
Ferrule; Sleeve for 0.75 mm<sup>2</sup> / AWG 20; uninsulated; electro-tin plated; silver-colored



**Item No.: 216-122**  
Ferrule; Sleeve for 0.75 mm<sup>2</sup> / AWG 20; uninsulated; electro-tin plated; silver-colored



**Item No.: 216-243**  
Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red



**Item No.: 216-263**  
Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red



**Item No.: 216-203**  
Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; red



**Item No.: 216-223**  
Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; red



**Item No.: 216-103**  
Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; uninsulated; electro-tin plated



**Item No.: 216-143**  
Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; uninsulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 1/08.92



**Item No.: 216-123**  
Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; uninsulated; electro-tin plated; silver-colored



1.1.2.1 Ferrule

|                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>Item No.: 216-204</b><br>Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; black                                                                          | <br><b>Item No.: 216-224</b><br>Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; black                                                                          | <br><b>Item No.: 216-244</b><br>Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; black             | <br><b>Item No.: 216-264</b><br>Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; black |
| <br><b>Item No.: 216-284</b><br>Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; black  | <br><b>Item No.: 216-124</b><br>Ferrule; Sleeve for 1.5 mm² / AWG 16; un-insulated; electro-tin plated                                                                              | <br><b>Item No.: 216-144</b><br>Ferrule; Sleeve for 1.5 mm² / AWG 16; un-insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 1/08.92; silver-colored | <br><b>Item No.: 216-104</b><br>Ferrule; Sleeve for 1.5 mm² / AWG 16; un-insulated; electro-tin plated; silver-colored                                                             |
| <br><b>Item No.: 216-289</b><br>Ferrule; Sleeve for 10 mm² / AWG 8; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red      | <br><b>Item No.: 216-209</b><br>Ferrule; Sleeve for 10 mm² / AWG 8; insulated; electro-tin plated; red                                                                              | <br><b>Item No.: 216-109</b><br>Ferrule; Sleeve for 10 mm² / AWG 8; un-insulated; electro-tin plated                                                                                           | <br><b>Item No.: 216-210</b><br>Ferrule; Sleeve for 16 mm² / AWG 6; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; blue    |
| <br><b>Item No.: 216-110</b><br>Ferrule; Sleeve for 16 mm² / AWG 6; un-insulated; electro-tin plated; brown metallic                                                                | <br><b>Item No.: 216-205</b><br>Ferrule; Sleeve for 2.08 mm² / AWG 14; insulated; electro-tin plated; yellow                                                                        | <br><b>Item No.: 216-206</b><br>Ferrule; Sleeve for 2.5 mm² / AWG 14; insulated; electro-tin plated; blue                                                                                      | <br><b>Item No.: 216-246</b><br>Ferrule; Sleeve for 2.5 mm² / AWG 14; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; blue  |
| <br><b>Item No.: 216-266</b><br>Ferrule; Sleeve for 2.5 mm² / AWG 14; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; blue  | <br><b>Item No.: 216-286</b><br>Ferrule; Sleeve for 2.5 mm² / AWG 14; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; blue  | <br><b>Item No.: 216-267</b><br>Ferrule; Sleeve for 4 mm² / AWG 12; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray               | <br><b>Item No.: 216-287</b><br>Ferrule; Sleeve for 4 mm² / AWG 12; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray   |
| <br><b>Item No.: 216-208</b><br>Ferrule; Sleeve for 6 mm² / AWG 10; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; yellow | <br><b>Item No.: 216-288</b><br>Ferrule; Sleeve for 6 mm² / AWG 10; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; yellow | <br><b>Item No.: 216-108</b><br>Ferrule; Sleeve for 6 mm² / AWG 10; un-insulated; electro-tin plated; silver-colored                                                                         |                                                                                                                                                                                                                                                                       |

1.1.3 Installation

1.1.3.1 Mounting accessories

|                                                                                                                                                                                 |                                                                                                                                                                                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>Item No.: 209-137</b><br>Mounting adapter; can be used as end stop; 6.5 mm wide; gray | <br><b>Item No.: 209-120</b><br>Mounting foot; can be snapped on terminal blocks with snap-in mounting foot; for mounting on relay-modules; 6.4 mm wide; gray |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

1.1.4 Jumper

1.1.4.1 Jumper



**Item No.: 262-402**  
Jumper; for conductor entry; 2-way; insulated; gray

1.1.5 Marking

1.1.5.1 Marking strip



**Item No.: 210-833**  
Marking strips; 25 m on roll; 6 mm wide; plain; Self-adhesive; white

1.1.6 Test and measurement

1.1.6.1 Testing accessories



**Item No.: 249-140**  
Test plug module; without locking device; modular; for 4-conductor terminal blocks; gray

1.1.7 Tool

1.1.7.1 Operating tool



**Item No.: 210-658**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; angled; short; multicoloured




**Item No.: 210-720**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured



**Item No.: 210-657**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; short; multicoloured


Installation Notes

Conductor termination



**CAGE CLAMP® connection**  
Inserting a conductor.  
With ferruled conductors, it is necessary to use a terminal block one size larger than the conductor's nominal cross-section.

Commoning



Commoning with comb-style jumper bar.


Installation




Mounting a terminal strip with snap-in feet into holes.




Mounting a terminal strip with snap-in feet onto aluminum rail.



Terminal strip with snap-in mounting feet  
Snapping a mounting foot (209-120).  
(Distance between mounting feet: approx. 25 ... 30 mm)




Terminal strip; with snap-in mounting feet; for DIN-35 rail



Terminal strip with snap-in mounting feet, for 0.6 ... 1.2 mm plate thickness, 3.5 mm mounting hole diameter (also for 210-154 Aluminum Rail or with 209-120 Mounting Foot for DIN-35 rail)

Marking



Marking with self-adhesive marking strips.



Marking by direct printing (upon request).