

## ToLEDo Retro GLS Dimmable

ToLEDo RT GLS V5 ST DIM 1521LM 827 E27 SL

0029320



### Product features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- Suitable replacement for incandescent and halogen lamps
- Gives same sparkling light effect as incandescent lamp
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment friendly - no mercury and lower CO2 emissions
- Dimmable with approved dimmers



## PRODUCT OVERVIEW

Product name	ToLEDo RT GLS V5 ST DIM 1521LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	11.2
Type	LED exchangeable
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740905
Warranty	3 years
Luminous flux (lm)	1521
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Wattage (W)	11.2
Dimmable	Yes
Average life (Nominal) (h)	15000
Product EAN number	5410288293202

## DATA TABLE

### General data

Product name	ToLEDo RT GLS V5 ST DIM 1521LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	11.2

## ToLEDo Retro GLS Dimmable

ToLEDo RT GLS V5 ST DIM 1521LM 827 E27 SL

0029320

Type	LED exchangeable
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-10°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740905
Warranty	3 years

### Optical data

Luminous flux (lm)	1521
Luminous flux (Rated) (lm)	1521
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	11.2
Equivalent watt (W)	100
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	Yes
Inrush Current (A)	1.5
Inrush Duration (µs)	520
Lamp Energy Label (class)	D
Max. products per 16A C Breaker	106
Max. products per 16A B Breaker	54

### Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Length (mm)	126
Nominal Product Diameter (mm)	70
Weight (kg)	0.046

### Packaging

Single packaging type	Carton
Product EAN number	5410288293202

## ToLEDo Retro GLS Dimmable

ToLEDo RT GLS V5 ST DIM 1521LM 827 E27 SL


0029320

Packaging single length / height (cm)	7.5
Packaging single width (cm)	7.5
Packaging single depth (cm)	14.0
DUN14 (outer)	15410288293209
Units per outer package	6
Packaging outer length / height (cm)	23.9
Packaging outer width (cm)	16.1
Packaging outer depth (cm)	15.5


### Safety data

Optimal operating condition (°C)	-10-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

## PHOTOMETRY



## TECHNICAL DRAWINGS




ToLEDo Retro GLS Dimmable  
*ToLEDo RT GLS V5 ST DIM 1521LM 827 E27 SL*  
0029320



**SYLVANIA**

0029320



**12**  
kWh/1000h




2019/2015

## ToLEDo Retro GLS Dimmable

ToLEDo RT GLS V5 ST DIM 1521LM 827 E27 SL  
0029320



0029320



**12**  
kWh/1000h



2019/2015