


Concord

OPTIX RECESSED 600x600 2L 4000K ALU DALI EM

2023576



Features

- OPTIX RECESSED 600x600 2L 4000K ALU DALI EM is a high efficacy low glare luminaire for office and education applications. Ceiling recessed 600x600 mm. Aluminised plastic extra low glare optics in 2 lines configuration. White RAL9016 fixture body. DALI dimmable. 3hr maintained emergency version. 4000K Neutral White LED, CRI>80, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 3400lm. Power consumption 26W. Luminaire efficacy 131lm/W. Lifespan: 48,500 hours L90B10. UGR<16, Luminance at 65°<200 Cd/m², IK07, IP20. Photobiological safety risk group 1. Electrical protection Class I. Glow wire test 850°C.

Product Overview

Product name	OPTIX RECESSED 600x600 2L 4000K ALU DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	3600
Luminous flux (lm)	3600
Luminaire efficacy (lm/W)	131
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG1

Concord
by SYLVANIA


Concord

OPTIX RECESSED 600x600 2L 4000K ALU DALI EM

2023576

Luminous flux (emergency) (lm)	80
Total power consumption (W)	26
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Product EAN number	5025768235766
Warranty	5 years
Dimming method	DALI
Useful luminous flux (#use)	3600

Photometry



Technical drawings

