UFH-0605MDSS09: 9-groups Manif. ss ,adjust.+flow met.+thermo,fill+dr. val., arv 9way



Commercial information

- Adjustable flowmeters
- Adaptable brackets in composite
- Integrated air vent, drain and filling tap
- 1” connection with union nut
- Integrated control valves
- Compact design

Basic unit dimensions	
Height	190 mm
Length	620 mm
Width	120 mm
Net weight	4.000 kg

Certificates

Applications

Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✖	Medium temperature (continuous)	5|55 Degrees celsius
Material	Stainless steel	Max. operating pressure	6 Bar
Position primary connection	Left/right	Max. number of expansion groups	0
Primary connection	Internal thread cylindrical BSPP-G (ISO 228-1)	Number of groups secondary	9
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12|20 Millimetre
With valves on primary connection	✖	Flow-through capacity	0|5 Litre per hour
With mixing valve	✖	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	✖	Width	120 Millimetre
Multi-zone manifold	✖	Height	190 Millimetre
With temperature limit	✖	Depth	620 Millimetre
With non-return valve	✖		
With circulation pump	✖		
Article compression class	PN 6		
With controller	✖		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	✖		
Temperature measurement supply	None		
Temperature measurement return	None		
With de-aeration	✔		
With pressure gauge	✖		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✔		
With flow-through indicator	✔		
With thermal actuator	✖		
With wall-mounting bracket	✔		
With casing	✖		