

36P-2628P: Press adapter to copper press 26x28 cusi



Commercial information

- Press-fit adapter (M,V & SA Profile)
- Quick and more reliable solution than compression fittings
- M, V & SA-profile can be used on copper side.
- Can be used in concrete if the fitting is protected
- Can be used in spaces which are difficult to reach
- Brass CW724 "CuSi"
- Compatible with thin-walled steel, copper, stainless steel

Basic unit dimensions

Height	62 mm
Length	62 mm
Width	38 mm
Net weight	0.130 kg

Certificates

QB (CSTBat), DVGW Wasser, ÖVGW Wasser, SINTEF, KIWA, KOMO, ATG, ÖN EN 21003-2/-3, ETA, STF, AFNOR, ACS, WRAS, GOST-R, PZH, ITC, TSU, DNV-GL, RISE, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	26 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	28 Millimetre
Material connection 2	Brass	Length	62 Millimetre
Surface protection connection 2	Untreated	Wrench width	0 Millimetre
Surface treatment connection 2	Untreated	Wrench width union nut	0 Millimetre
Shape	Straight	Medium temperature (continuous)	-10 70 Degrees celsius
Reducing	✗	Max. operating pressure at 20 °C	10 Bar
Eccentric	✗	Standard Dimension Ratio (SDR)	0
System specific	✓		
Connection 1	Press sleeve		
Connection 2	Press sleeve		
Contour code connection 2	M/F (seal) (expired)		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		