

VB060503-BLAUW: Manifold 1" with ball valves - 3 EK-conections Blue



Commercial information

Brass Henco distributor 1" connection with ball valve and eurocone connections

- Universal eurocone connections
- Lockable per group
- Short installation length
- Can be installed both horizontally and vertically as upside down

Available in a 3/4" and a 1" version

Available in blue and red.

Suitable for heating, air conditioning and sanitary installations.

Via configuration distributor possibility of parallel use of cold and/or hot circuits.

Basic unit dimensions

Height	75 mm
Length	150 mm
Width	50 mm
Net weight	0.597 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Suitable for tap water	✓	Number of branches	3
Suitable for central heating water	✓	Number of branching directions	1
Suitable for cooling water	✓	Distance between offset	50 Millimetre
Suitable for compressed air	✗	Max. medium temperature (continuous)	95 Degrees celsius
Suitable for glycol	✓	Width	50 Millimetre
Mounting method	Surface mounting	Height	75 Millimetre
Model	Distributor/collector	Length distributor	150 Millimetre
Material	Brass		
Surface protection	Galvanised		
Shape	Throughflow with straight branches		
Nominal diameter connection 2	1 inch (25)		
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)		
Nominal diameter branches	3/4 inch (20)		
Connection branches	Euroconus standardless		
Deviant distance between branches	✗		
With filling/drain tap	✗		
System specific	✓		
With shut-off valve	✓		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With insulation	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		