

Blanking flange PN 16 for globe valve for conversion to 2-way valve

- incl. gasket


Type Overview

Type	DN	Number of Bolt Holes	Suitable for	Weight
ZH715	15	4	H711N...H715N	1.2 kg
ZH720	20	4	H720N	1.5 kg
ZH725	25	4	H725N	1.7 kg
ZH732	32	4	H732N	2.4 kg
ZH740	40	4	H740N	2.7 kg
ZH750	50	4	H750N	3.6 kg
ZH765	65	4	H764N/H765N	4.2 kg
ZH780	80	8	H779N/H780N	5.6 kg
ZH7100	100	8	H7100N	7.0 kg
ZH7125	125	8	H7125N	9.1 kg
ZH7150	150	8	H7150N	13 kg

Technical data

Materials Flange Steel painted RAL5002

Safety notes



- This accessory has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied during installation.
- The accessory may not be disposed of as household refuse. All locally valid regulations and requirements must be observed.

General notes

Delivery notes In the ZH7.. scope of delivery: blanking flange, Sk screws with nut, gasket

Dimensions

Dimensional drawings



Type	C [mm]	d [mm]	K [mm]	D [mm]
ZH715	14	4 x 14	65	95
ZH720	16	4 x 14	75	105

Type	C [mm]	d [mm]	K [mm]	D [mm]
ZH725	16	4 x 14	85	115
ZH732	16	4 x 18	100	140
ZH740	16	4 x 18	110	150
ZH750	18	4 x 18	125	165
ZH765	18	4 x 18	145	185
ZH780	20	8 x 18	160	200
ZH7100	20	8 x 18	180	220
ZH7125	22	8 x 18	210	250
ZH7150	22	8 x 22	240	285