


V-050404-Z: Manifold 3/4", 1/2"-female thread without air vent hole, 3/4" 4x1/2"



Commercial information

Brass distributor 3/4" without vent opening with number of 1/2" connections

Basic unit dimensions

Height	35 mm
Length	202 mm
Width	35 mm
Net weight	0.742 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Suitable for tap water	✓	Number of branches	4
Suitable for central heating water	✓	Number of branching directions	1
Suitable for cooling water	✓	Distance between offset	50 Millimetre
Suitable for compressed air	✗	Max. medium temperature (continuous)	95 Degrees celsius
Suitable for glycol	✓	Width	35 Millimetre
Mounting method	Surface mounting	Height	35 Millimetre
Model	Distributor/collector	Depth	31 Millimetre
Material	Brass	Length distributor	202 Millimetre
Surface protection	Untreated		
Shape	Throughflow with straight branches		
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)		
Nominal diameter branches	1/2 inch (15)		
Connection branches	Internal thread cylindrical BSPP-G (ISO 228-1)		
Deviant distance between branches	✗		
With filling/drain tap	✗		
System specific	✓		
With shut-off valve	✗		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With insulation	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		