

STERLING IP65 IK10 1325LM 830 SILVER

Item No: 4063833


Concord



Led exterior bulkhead, Unique feature allowing a choice between High Output or High Efficiency with the flick of a switch, 684/1325LM, 9/17W, 76/78LM/W, 3000K, Driver Current: 350/750mA, CRI80, Non dimmable, IP65, IK10, lifespan 100,000hrs (L70:B50), (HxWxD) 350 x 350 x 128mm, 3.4kg, 3 step MacAdam ellipse, RAL 9006, Class 1, 230V

Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	E _{0°} [lx]	E _{10°} [lx]	E _{30°} [lx]
0.5	1.52	899	72	12
1.0	3.04	217	18	3
1.5	4.57	97	8	1
2.0	6.09	54	5	0.8
2.5	7.61	35	3	0.5
3.0	9.13	24	2	0.3

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 113.4°)



STERLING IP65 IK10 1325LM 830 SILVER

Item No: 4063833

Concord

General data

Product name	STERLING IP65 IK10 1325LM 830 SILVER
Technology	LED
Cap/Base	N/A
Environment	Indoor, Outdoor
General application	Education, Hospitality, Logistics & Industry, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+35°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4579259
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	1325
Fixture luminous flux (lm)	1325
Luminaire efficacy (lm/W)	78
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	17
Primary Supply/Product voltage - min (V)	230.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
Electrical protection	Class I
Dimmable	No
Drive current (mA)	700
Inrush Current (A)	17
Inrush Duration (µs)	199
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	38
Max. products per 13A C Breaker	50
Max. products per 16A C Breaker	61
Max. products per 20A C Breaker	78
Max. products per 10A B Breaker	23
Max. products per 13A B Breaker	30
Max. products per 16A B Breaker	37
Max. products per 20A B Breaker	47

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	68500

Physical data

Housing colour	Silver
IP rating	IP65
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	128
Nominal Product Diameter (mm)	350
Weight (kg)	3.4

STERLING IP65 IK10 1325LM 830 SILVER

Item No: 4063833

Concord

Packaging

Product EAN number	5026524638333
Packaging single length / height (cm)	36.0
Packaging single width (cm)	36.0
Packaging single depth (cm)	13.5
DUN14 (inner)	05026524638333
Units per outer package	1
Packaging outer length / height (cm)	36.0
Packaging outer width (cm)	36.0
Packaging outer depth (cm)	13.5

Safety data

Optimal operating condition (°C) | -20-35