

Sterling Bulkhead - LED

STERLING IP65 IK10 1325LM 830 SILVER
4063833



Product features

- Led exterior bulkhead, Unique feature allowing a choice between High Output or High Efficiency with the flick of a switch, die-cast aluminium body, 684/1325LM, 9/17W, 76/78LM/W, 3000K, Driver Current: 350/750mA, CRI80, Non dimmable, IP65, IK10, lifespan 100,000hrs (L70:B50), (HxWxD) 350 x 350 x 128mm, 3.4kg, 3 step MacAdam ellipse, RAL 9006, Class 1, 230V, energy class: A++, A+, A



PRODUCT OVERVIEW

Product name	STERLING IP65 IK10 1325LM 830 SILVER
Technology	LED
Cap/Base	N/A
Environment	Indoor, Outdoor
General application	Education, Hospitality, Logistics & Industry, Office, Residential & Consumer, Retail
ETIM Class	EC002892
E-number FI	4579259
Warranty	5 years
Fixture luminous flux (lm)	1325
Luminaire efficacy (lm/W)	78
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Photobiological Risk Group	RG1
Total power consumption (W)	17
Electrical protection	Class I
Dimmable	No
Housing colour	Silver
IP rating	IP65
IK rating	IK10
Product EAN number	5026524638333

PHOTOMETRY

Sterling Bulkhead - LED



STERLING IP65 IK10 1325LM 830 SILVER
4063833

Distance [m]	Cone diameter [m]	E (0°)	E (C0)	E (C180)	Illuminance [lx]
0.5	1.52	507	507	507	499
1.0	3.04	507	507	507	121
1.5	4.57	507	507	507	97
2.0	6.09	507	507	507	74
2.5	7.61	507	507	507	59
3.0	9.13	507	507	507	47

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 112.4°)

Distance [m]	Cone diameter [m]	E (0°)	E (C0)	E (C180)	Illuminance [lx]
0.5	1.55	507	507	507	122
1.0	3.10	507	507	507	31
1.5	4.65	507	507	507	19
2.0	6.21	507	507	507	14
2.5	7.76	507	507	507	11
3.0	9.31	507	507	507	9

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 114.4°)



TECHNICAL DRAWINGS

