

Wall mounted receptacle DUO

Part no. 5690A




- screw terminals
- **X-CONTACT**
- switched
- mechanical DUO-interlock
- upon request with provision for an additional padlock

Technical specifications

| | |
|-----------------------|-----------------|
| Ampere | 125 A |
| Poles | 4 p |
| Voltage | 500 V |
| Clock position | 7 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | X-CONTACT |
| Protection type | IP67 |
| Enclosure material | Plastic |
| Weight | 7817 g |
| Certifications | CQC |

Drawing



| Drawing 1 MB 177 | Amp. Poles | 125 | | |
|---|---------------|---------|---------|---------|
| | | 3 | 4 | 5 |
| Dim. in mm | a | 460 | 460 | 460 |
| | b | 260 | 260 | 260 |
| | c | 270 | 270 | 270 |
| | d | 434 | 434 | 434 |
| | e | 234 | 234 | 234 |
| | f | 11 | 11 | 11 |
| | g | 9 | 9 | 9 |
| | h | 519 | 519 | 519 |
| | M | 63 | 63 | 63 |
| | M* | 2x63 | 2x63 | 2x63 |
| Max. cable diam. (mm) | | 44 | 44 | 44 |
| Terminal for cond. cross section (mm ²) min.-max. | | 25 — 70 | 25 — 70 | 25 — 70 |