
Technical data sheet

3-wire connection cable, PVC, cross-section 2.5 mm², 5 m length, white
Item number: 6108720



Connection cable 3 x 2.5 mm² in the version socket-connector, type WINSTA® MIDI.

PVC hose pipe: H05VV-F 3 x 2.5 mm²
Suitable for connection of ready-for-connection universal supports Connect UTC to an energy distributor.


CE

PA Polyamide

Master data

Item number	6108720
Type	VL-WIN 3P2.5 5W
Description 1	Connection cable
Description 2	3x2,5mm², WINSTA
Manufacturer	OBO
Dimension	5000x27x15
Colour	White
Material	Polyamide
Smallest sales unit	1
Unit of quantity	Piece
Weight	82 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	2,9358 kg CO2e / 1 Piece

Dimensions



Technical data sheet

3-wire connection cable, PVC, cross-section 2.5 mm², 5 m length, white
Item number: 6108720

Technical data

Number of poles	3
Type of terminated cable	Connection cable
Type of locking	Separate
Version, page 1	socket
Version, page 2	Connector
Rated surge voltage	4
Fire load	3.83
Colour of the coding/contact insert	White
Halogen-free	no
Cable type	H05VV-F
Cable length	5000 mm
Jacket colour	White
Mechanical encoding	yes
Nominal voltage	250 V
Nominal current	20 A
Pin labelling	L, N, PE
Cross-section	1.5 mm²
ROHS-conformant	yes
Protection rating	IP20
Degree of soiling	3