

AK-EK05VD: Adapter eurocone 3/4" to flat sealing



Commercial information

Kunststoffen overgangsstuk om van euroconus 3/4" te gaan naar vlakdichtend

Basic unit dimensions

| | |
|------------|----------|
| Height | 9 mm |
| Length | 20 mm |
| Width | 20 mm |
| Net weight | 0.002 kg |

Certificates

Applications

Heating

Solutions

Building installations, Industry, Utility

Technical characteristics

| | | | |
|----------------------------|-------------------|---------------------------------|------------------------|
| Material connection 1 | Plastic (expired) | Bend radius | 0 Millimetre |
| Material connection 2 | Plastic (expired) | Length | 20 Millimetre |
| Reducing | ✘ | Medium temperature (continuous) | -10 70 Degrees celsius |
| Eccentric | ✘ | Standard Dimension Ratio (SDR) | 0 |
| System specific | ✓ | | |
| Main colour fitting | Green | | |
| Self-sealing | ✘ | | |
| Ring stiffness class | Other | | |
| With sealing rings/gaskets | ✘ | | |
| Capped | ✘ | | |
| With drain valve | ✘ | | |
| FM quality mark | ✘ | | |
| LPCB quality mark | ✘ | | |
| ULC quality mark | ✘ | | |
| UL quality mark | ✘ | | |
| VdS quality mark | ✘ | | |
| KIWA certified | ✘ | | |
| Gastec QA mark | ✘ | | |