

# Adaptor 2 for data outlet(s)

170-65201



Adaptor 2 can be used for the installation of 1 outlet and can be used for Systimax and others.

## Technical data

Adaptor 2 for data outlet(s)

The adaptor has the indelible engraving 2 on the front and back. The adaptor 2 is suitable for integrating 1 outlet of the brands Systimax, among others. The outlet is clicked into the adapter along the back. The adapter is made of dark grey PC+ASA, complies with a filament test of 650°C and is halogen-free. On each of its 4 corners, the base is equipped with studs that ensure that the central plate is perfectly positioned in relation to the base. The adapter is equipped with snap hooks on the right and left sides that hold the central plate in place. The adapter 2 can be clicked onto a mounting frame 45x45mm or a trunking system with a 45 mm cover height. You can either centrally mount 1 adaptor, or click 2 adaptors next to each other. Depending on the selected option, it can be finished with a flat central plate for 1 outlet or a flat central plate for 2 outlets (with or without a transparent text field). When combining 2 adaptors, adaptor 2 can be integrated in a 45x45 opening in the empty mini-patch distribution board: Dimensions adaptor 2: 22.5x45mm

- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 20.7 mm x 44.8 mm x 20.1 mm
- Marking: CE

