



8HNA-PK32: Henco Press 75x32



Commercial information

The Super Size range includes the Henco multilayer pipe and Henco fittings with diameters of 75-90, with reducers to diameters of 32-40-50-63. The connectors ensure a complete multilayer pipe system with numerous variations for headers and risers. The many combination possibilities and the revolutionary connection technology make this modular system extremely flexible.

Like all Henco press fittings, the Super Size fittings come with leak detection and are made from high-performance plastic PVDF. These properties make the Henco Super Size fittings suited for different applications, such as drinking water installations, heating installations and installations in the chemical and food industries.

Basic unit dimensions

Height	63 mm
Length	78 mm
Width	78 mm
Net weight	0.071 kg

Certificates

KIWA, KOMO, DVGW Wasser, ATG, WRAS, STF, ETA, SINTEF, RISE

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend radius	0 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Outer pipe diameter connection 1	75 Millimetre
Shape	Straight	Outer pipe diameter connection 2	32 Millimetre
Reducing	✓	Length	78 Millimetre
Eccentric	✗	Medium temperature (continuous)	-10 70 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	10 Bar
Connection 1	Press sleeve	Standard Dimension Ratio (SDR)	0
Connection 2	Press sleeve		
Main colour fitting	Black		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
Self-sealing	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✗		
Capped	✗		
With drain valve	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
VdS quality mark	✗		
KIWA certified	✓		
Gastec QA mark	✗		