

## Wall mounted receptacle DUO

Part no. 5643A




- screw terminals
- X-CONTACT
- switched
- mechanical DUO-interlock
- DIN rail
- receptacles can be padlocked

### Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 63 A            |
| Poles                 | 5 p             |
| Voltage               | 400 V           |
| Clock position        | 6 h             |
| Hertz                 | 60-50 Hz        |
| Connection technology | Screw terminals |
| Contact               | X-CONTACT       |
| Protection type       | IP67            |
| Enclosure material    | Plastic         |
| Weight                | 3820 g          |

### Drawing



| Drawing<br>1 MB 181/620 | Amp.<br>Poles   | 16    |       |       | 32    |       | 63   |      |
|-------------------------|---|-------|-------|-------|-------|-------|------|------|
|                         |   | 3     | 4     | 5     | 4     | 5     | 4    | 5    |
| Dim. in mm              | a   | 364   | 364   | 364   | 364   | 364   | 460  | 460  |
|                         | b   | 134   | 134   | 134   | 134   | 134   | 180  | 180  |
|                         | c   | 160   | 162   | 163   | 168   | 168   | 202  | 202  |
|                         | d   | 347   | 347   | 347   | 347   | 347   | 440  | 440  |
|                         | e   | 117   | 117   | 117   | 117   | 117   | 160  | 160  |
|                         | f   | 6.3   | 6.3   | 6.3   | 6.3   | 6.3   | 8.1  | 8.1  |
|                         | g   | 8     | 8     | 8     | 8     | 8     | 8    | 8    |
|                         | h   | 391   | 395   | 398   | 408   | 411   | 505  | 505  |
|                         | M   | 32/40 | 32/40 | 32/40 | 32/40 | 32/40 | 40   | 40   |
|                         | M*  | 2x32  | 2x32  | 2x32  | 2x32  | 2x32  | 2x40 | 2x40 |
|                         | Max. cable diam. (mm)   | 27    | 27    | 27    | 27    | 27    | 27   | 27   |
|                         | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1.5   | 1.5   | 1.5   | 2.5   | 2.5   | 6    | 6    |
|                         |   | -4    | -4    | -4    | -10   | -10   | -25  | -25  |