


LIFESAFE PRO DOWNLIGHT RA R EM3 NM DA BK
0038802



Features

• LiFeSafe PRO Downlight RA R EM3 NM DA BK is a black miniature DALI addressable emergency recessed downlight with interchangeable optics for open area and escape route illumination. Non-maintained self-test 3Hr emergency duration with LiFePO4 rechargeable battery. Quick and easy installation with driver module and battery pack contained in articulated case that can pass through 44-50mm cut-out. Suitable for ceiling thickness 5-15mm. 225lm (open area) / 200lm (corridor), 3.5W, IK03, IP20. Class II electrical construction. 6-year warranty

Product Overview

Product name	LIFESAFE PRO DOWNLIGHT RA R EM3 NM DA BK
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Light source included	0038802
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	225
Luminous flux (lm)	225
Luminaire efficacy (lm/W)	64
Correlated colour temperature (k)	5000
CRI (Ra)	70
Photobiological Risk Group	RG2
Luminous flux (emergency) (lm)	225
Luminous flux (emergency) (lm)	225
Electrical protection	Class II

LIFESAFE PRO DOWNLIGHT RA R EM3 NM DA BK
0038802

Control gear type	LED driver constant current
Housing colour	Black
IP rating	IP20
IK rating	IK03
Product EAN number	5410288388021
Warranty	6 years

Technical drawings

