



Features

- LiFeSafe PRO SURF RDDL RA C EM3 NM DA is a DALI addressable round surface mount standalone luminaire. Non-maintained DALI 3Hr emergency duration with LiFePO4 rechargeable batteries. Interchangeable lens for open area or corridor beam. System power 3.5W , 240lm (open area) / 200lm (corridor), 20mm conduit entry points, IK06, IP20, Class II construction 6-year warranty.

Product Overview

Product name	LIFESAFE PRO SURF RDDL RA RC EM3 NM DA
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Light source included	0038810
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	240
Luminous flux (lm)	240
Luminaire efficacy (lm/W)	80
Correlated colour temperature (k)	5000
CRI (Ra)	70
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	240
Luminous flux (emergency) (lm)	240
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP20



LIFESAFE PRO SURF RDDL RA RC EM3 NM DA
0038810

IK rating	IK06
Product EAN number	5410288388106
Warranty	6 years

Technical drawings

Surface Mount

