



Features

• LiFeSafe PRO SURF RDDLHO RA C EM3 NM DA is a high output DALI addressable round surface mount standalone luminaire. Non-maintained self-test 3Hr emergency duration with LiFePO4 rechargeable batteries. Interchangeable lens for open area or corridor beam. 3.5W - 450lm, 20mm conduit entry points, IK06, IP20, Class II construction 6-year warranty.

Product Overview

Product name	LIFESAFE PRO SURF RDDL HO RARC EM3 NM DA
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Light source included	0038811
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	450
Luminous flux (lm)	450
Luminaire efficacy (lm/W)	75
Correlated colour temperature (k)	5000
CRI (Ra)	70
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	450
Luminous flux (emergency) (lm)	450
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	White

LIFESAFE PRO SURF RDDL HO RARC EM3 NM DA
0038811

IP rating	IP20
IK rating	IK06
Product EAN number	5410288388113
Warranty	6 years

Technical drawings

Surface Mount

