




Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Angle	90 Degrees
Material quality connection 1	Other	Outer pipe diameter connection 1	20 Millimetre
Surface protection connection 1	Untreated	Wall thickness, connection 1	2.25 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	16 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Wall thickness, connection 2	2.25 Millimetre
Material quality connection 2	Other	Outer pipe diameter connection 3	20 Millimetre
Surface protection connection 2	Untreated	Wall thickness, connection 3	2.25 Millimetre
Surface treatment connection 2	Untreated	Wrench width	0 Millimetre
Material connection 3	Polyvinylidene fluoride (PVDF)	Max. operating pressure at 20 °C	10 Bar
Material quality connection 3	Other	Wrench width union nut	0 Millimetre
Surface protection connection 3	Untreated	Max. operating pressure at max. medium temperature	10 Bar
Surface treatment connection 3	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Model	T-piece	Standard Dimension Ratio (SDR)	0
Swept entry type (with inner radius)	✗		
Reducing	✓		
System specific	✓		
Nominal diameter connection 1	DN 15		
Connection 1	Insert (push-fitting)		
Contour code connection 1	Other		
Nominal diameter connection 2	DN 12		
Connection 2	Insert (push-fitting)		
Contour code connection 2	Other		
Nominal diameter connection 3	DN 15		
Connection 3	Insert (push-fitting)		
Contour code connection 3	Other		
Flange compression class	PN 10		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	White		
High tensile strength	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
With drain valve	✗		
With de-aerator	✗		
With thermal insulation	✗		
With buffer stud	✗		
Capped	✗		
With connection indicator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		

Related products

Product code	GTIN	Description	Image
VISION-KEY16	05414764010376	Henco Vision key Ø16	
VISION-KEY20	05414764010376	Henco Vision key Ø20	
SK-STOPCLIP16	05414764010376	Henco Reusable stop and clip for push fit connection Ø16	
SK-STOPCLIP20	05414764010376	Henco Reusable stop and clip for push fit connection Ø20	