





Technical characteristics

| | | | |
|--------------------------------------|--|--|------------------------|
| Material connection 1 | Polyvinylidene fluoride (PVDF) | Angle | 90 Degrees |
| Material quality connection 1 | Other | Outer pipe diameter connection 1 | 26 Millimetre |
| Surface protection connection 1 | Untreated | Wall thickness, connection 1 | 2.35 Millimetre |
| Surface treatment connection 1 | Untreated | Outer pipe diameter connection 2 | 16 Millimetre |
| Material connection 2 | Polyvinylidene fluoride (PVDF) | Wall thickness, connection 2 | 2.25 Millimetre |
| Material quality connection 2 | Other | Outer pipe diameter connection 3 | 26 Millimetre |
| Surface protection connection 2 | Untreated | Wall thickness, connection 3 | 2.35 Millimetre |
| Surface treatment connection 2 | Untreated | Wrench width | 0 Millimetre |
| Material connection 3 | Polyvinylidene fluoride (PVDF) | Max. operating pressure at 20 °C | 10 Bar |
| Material quality connection 3 | Other | Wrench width union nut | 0 Millimetre |
| Surface protection connection 3 | Untreated | Max. operating pressure at max. medium temperature | 10 Bar |
| Surface treatment connection 3 | Untreated | Medium temperature (continuous) | -10 70 Degrees celsius |
| Model | T-piece | Standard Dimension Ratio (SDR) | 0 |
| Swept entry type (with inner radius) | ✗ | | |
| Reducing | ✓ | | |
| System specific | ✓ | | |
| Nominal diameter connection 1 | DN 20 | | |
| Connection 1 | Insert (push-fitting) | | |
| Contour code connection 1 | Other | | |
| Nominal diameter connection 2 | DN 12 | | |
| Connection 2 | Insert (push-fitting) | | |
| Contour code connection 2 | Other | | |
| Nominal diameter connection 3 | DN 12 | | |
| Connection 3 | Insert (push-fitting) | | |
| Contour code connection 3 | Other | | |
| Flange standard | Other | | |
| Material sealing | Ethylene-propylene diene monomer rubber (EPDM) | | |
| Main colour fitting | White | | |
| High tensile strength | ✗ | | |
| Ring stiffness class | Other | | |
| With sealing rings/gaskets | ✓ | | |
| With drain valve | ✗ | | |
| With de-aerator | ✗ | | |
| With thermal insulation | ✗ | | |
| With buffer stud | ✗ | | |
| Capped | ✗ | | |
| With connection indicator | ✗ | | |
| FM quality mark | ✗ | | |
| LPCB quality mark | ✗ | | |
| ULC quality mark | ✗ | | |
| UL quality mark | ✗ | | |
| DIN-CERTCO certificate | ✗ | | |
| VdS quality mark | ✗ | | |
| With approval for TÜV | ✗ | | |
| DVGW quality mark for gas | ✗ | | |
| DVGW quality mark for water | ✓ | | |
| KIWA certified | ✓ | | |
| Gastec QA mark | ✗ | | |
| KOMO certified | ✓ | | |
| Type approval according to BBR/EKS | ✗ | | |

Related products

| Product code | GTIN | Description | Image |
|---------------|----------------|--|---|
| VISION-KEY16 | 05414764010413 | Henco Vision key Ø16 |  |
| VISION-KEY26 | 05414764010413 | Henco Vision key Ø26 |  |
| SK-STOPCLIP16 | 05414764010413 | Henco Reusable stop and clip for push fit connection Ø16 |  |
| SK-STOPCLIP26 | 05414764010413 | Henco Reusable stop and clip for push fit connection Ø26 |  |