

Technical data sheet

Junction box, T 60, with strain relief entries IP 31



Item number: 2007803



Junction box with strain relief entries for the connection of cables indoors and in protected outdoor areas. Square design with knock-out entries to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting and on mounting panels. With the option of fastening inside and to mount via the corner domes. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK07 according to DIN EN 50102.



PP Polypropylene

Master data

| | |
|------------------------------------|----------------------------|
| Item number | 2007803 |
| Type | T 60 ZE IP30 |
| Description 1 | Junction box |
| Description 2 | with strain relief entries |
| Manufacturer | OBO |
| Dimension | 114x114x57 |
| Colour | Light grey; RAL 7035 |
| Material | Polypropylene |
| Smallest sales unit | 5 |
| Unit of quantity | Piece |
| Weight | 11.2 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,4739 kg CO2e / 1 Piece |

Technical data sheet

Junction box, T 60, with strain relief entries IP 31




Item number: 2007803

Dimensions



| | |
|--------|--------|
| Length | 114 mm |
| Width | 114 mm |
| Height | 67 mm |



Technical data

| | |
|-----------------------------------|--|
| Expandable | yes |
| No. of entries | 7 |
| Type of entry | Strain relief entries for direct penetrations for cable diameters of 7-21 mm |
| Type of entry | Cable |
| Type of housing penetration | Pre-marking |
| Measured insulation voltage V_i | 500 V |
| Equipment | Without |
| Cover | Not transparent |
| Cover fastening | Screwed |
| Entry from rear | yes |
| Entries | 7 |
| Explosion-tested version | no |
| Flame-resistant | acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C |
| Shape | Square |
| Maintain electrical functions | Without |
| For Ex zone | Without |
| For Ex zone gas | Without |
| For Ex zone dust | Without |
| Halogen-free | yes |
| Clear internal dimensions | 100x100x48 mm |
| With screening | no |
| with lid | yes |
| Mounting type | Wall/ceiling mounting |
| Nominal cross-section, min. | 6 mm ² |
| Nominal voltage | 500 V |
| Sealable | yes |
| Protection rating | IP30 |
| Protection rating IK code | IK07. |
| Permitted temperature range, max. | 65 °C |
| Permitted temperature range, min. | -25 °C |
| Transparent lid | no |
| Weatherproof | no |