


## UFH-0605MDSS15: 15-groups Manif. ss ,adjust.+flow met.+thermo,fill+dr. val., arv 15way



### Commercial information

- Adjustable flowmeters
- Adaptable brackets in composite
- Integrated air vent, drain and filling tap
- 1" connection with union nut
- Integrated control valves
- Compact design

### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 190 mm   |
| Length     | 970 mm   |
| Width      | 120 mm   |
| Net weight | 6.000 kg |

### Certificates

### Applications

Underfloor Heating

### Solutions

Underfloor heating, Building installations, Industry, Utility

## Technical characteristics

|                                       |                                                |                                                |                      |
|---------------------------------------|------------------------------------------------|------------------------------------------------|----------------------|
| Connection type primary side          | 2-pipe                                         | Outer pipe diameter primary connection         | 32 Millimetre        |
| Suitable for cooling                  | ✗                                              | Medium temperature (continuous)                | 5 55 Degrees celsius |
| Material                              | Stainless steel                                | Max. operating pressure                        | 6 Bar                |
| Position primary connection           | Left/right                                     | Max. number of expansion groups                | 0                    |
| Primary connection                    | Internal thread cylindrical BSPP-G (ISO 228-1) | Number of groups secondary                     | 15                   |
| Nominal diameter primary connection   | 1 inch (25)                                    | Outer pipe diameter secondary                  | 12 20 Millimetre     |
| With valves on primary connection     | ✗                                              | Flow-through capacity                          | 0 5 Litre per hour   |
| With mixing valve                     | ✗                                              | Min. pressure difference secondary flow/return | 0 Kilo Pascal        |
| Expandable                            | ✗                                              | Width                                          | 120 Millimetre       |
| Multi-zone manifold                   | ✗                                              | Height                                         | 190 Millimetre       |
| With temperature limit                | ✗                                              | Depth                                          | 970 Millimetre       |
| With non-return valve                 | ✗                                              |                                                |                      |
| With circulation pump                 | ✗                                              |                                                |                      |
| Article compression class             | PN 6                                           |                                                |                      |
| With controller                       | ✗                                              |                                                |                      |
| Hydraulic balance control             | None                                           |                                                |                      |
| Volume flow measurement               | Analogue                                       |                                                |                      |
| With thermometer                      | ✗                                              |                                                |                      |
| Temperature measurement supply        | None                                           |                                                |                      |
| Temperature measurement return        | None                                           |                                                |                      |
| With de-aeration                      | ✓                                              |                                                |                      |
| With pressure gauge                   | ✗                                              |                                                |                      |
| Secondary connection                  | Euroconus standardless                         |                                                |                      |
| Nominal diameter secondary connection | 3/4 inch (20)                                  |                                                |                      |
| Closable groups                       | ✓                                              |                                                |                      |
| With flow-through indicator           | ✓                                              |                                                |                      |
| With thermal actuator                 | ✗                                              |                                                |                      |
| With wall-mounting bracket            | ✓                                              |                                                |                      |
| With casing                           | ✗                                              |                                                |                      |