


Concord

BEACON XL 93CRI 4K WIDE BEAM L3 ON-BOARD DIM BLACK 2059708



Features

- Integrated LED spotlight, black RAL 9005, compact and minimalist design, ideal for retail, display, museum and gallery applications, die-cast aluminium body, passive cooling heatsink, beam angle: 50° wide beam, optics: Polycarbonate lens, colour temperature: 4000K neutral white, total system power: 33W, total fixture output: 3033lm, luminaire efficacy: 92lm/W, LOR: 100%, colour rendering: Ra 93 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 850mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø113x165x205mm, weight: 1.66kg.

Product Overview


Product name	BEACON XL 93CRI 4K WIDE BEAM L3 ON-BOARD DIM BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
E-number FI	4280868
Fixture luminous flux (lm)	3033
Luminaire efficacy (lm/W)	92
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White

Concord


BEACON XL 93CRI 4K WIDE BEAM L3 ON-BOARD DIM BLACK 2059708

CRI (Ra)	93
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	33
Electrical protection	Class II
Control gear type	Electronic ballast
Housing colour	Black
IP rating	IP20
IK rating	IK02
Product EAN number	5025768597086
Warranty	5 years

Photometry



Technical drawings



Concord

BEACON XL 93CRI 4K WIDE BEAM L3 ON-BOARD DIM BLACK 2059708

Data table

GENERAL DATA

Product name	BEACON XL 93CRI 4K WIDE BEAM L3 ON-BOARD DIM BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
Performance ambient temperature Tq (°C)	25
E-number FI	4280868
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3033
Luminaire efficacy (lm/W)	92
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	93
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	33
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.9
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast

Concord

BEACON XL 93CRI 4K WIDE BEAM L3 ON-BOARD DIM BLACK 2059708

Drive current (mA)	850
Inrush Current (A)	5
Inrush Duration (µs)	50
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	52

LIFETIME DATA

Lifespan L70 B50	72000
Lifespan L80 B20	72000
Lifespan L90 B10	33000

PHYSICAL DATA

Housing colour	Black
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	85
Nominal Product Width (mm)	165
Weight (kg)	1.365

PACKAGING

Single packaging type	Carton
Product EAN number	5025768597086
Packaging single width (cm)	19.5
Packaging single depth (cm)	20.0
DUN14 (outer)	05025768597086
Packaging outer length / height (cm)	25.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No

Concord

BEACON XL 93CRI 4K WIDE BEAM L3 ON-BOARD DIM BLACK
2059708

Suitable for household illumination

No