

## PRODUCT DATASHEET

**Type:** LAVABATH3-GL-SMART-600-PWS  
**Art. Nr.:** 46336



9120129931427

### Short description

SMART infrared bathroom heater, pure white satinized glass, 160x50cm,



### Product Description

The LAVA BATH 3.0 SMART is the ideal infrared heater with integrated SMARTBOX (control unit) and accompanying SMARTCUBE (wireless thermostat) for convenient control via the ETHERMA SMART app for use in bathrooms. It combines efficient heat emission with elegant design and practical functions. The surface made of 5 mm thick ESG safety glass not only looks elegant, but is also extremely robust and heat-resistant. An integrated temperature limiter in each panel ensures safe operation. The frameless design gives the device a modern, timeless appearance that blends harmoniously into any bathroom environment. The innovative technology of the LAVA BATH 3.0 transforms the glass surface into a powerful radiant emitter. In combination with even heat distribution on the front and optimally insulated rear, a high level of radiant efficiency is achieved. This creates pleasant, direct infrared heat in the room within a short time. The maximum surface temperature is 70°C – ideal for cozy bathroom warmth. Particularly practical: the chrome-plated, single-sided towel rail supplied as standard ensures pleasantly preheated towels. Up to two additional rails can be added as an option to further increase comfort. The LAVA BATH 3.0 is designed for vertical wall mounting and is available in five different power levels to suit different room sizes and heating requirements. Available in pure white, satin white, or mirror finish. Protection class: IP X4. Surface: ESG safety glass, 5 mm. Surface temperature: max. 70 °C. Connection cable: 1 m, 3×1.0 mm<sup>2</sup> without plug. CE compliant.

### ETIM 10 Characteristics

<b>Type of IR radiation</b>	IR-C	<b>Power consumption</b>	600 Watt
<b>Mounting method</b>	Surface mounting	<b>Supply voltage</b>	230 230 Volt
<b>Mounting direction</b>	Vertical	<b>Frequency supply voltage</b>	50 50 Hertz
<b>Suitable for ceiling mounting</b>	✘	<b>Max. surface temperature</b>	70 Degrees celsius
<b>Degree of protection (IP)</b>	IPX4	<b>Height</b>	1600 Millimetre
<b>Colour</b>	White	<b>Width</b>	500 Millimetre
<b>With imprint</b>	✘	<b>Depth</b>	55 Millimetre
<b>With room temperature controller</b>	✓	<b>RAL-number</b>	0
<b>With mounting material</b>	✓		
<b>With frame</b>	✘		
<b>Material frame</b>	Other		
<b>Colour frame</b>	Other		
<b>Surface treatment</b>	Other		
<b>Surface structure front panel</b>	Smooth		
<b>With lighting cove</b>	✘		
<b>Dimmable</b>	✘		
<b>Light outlet</b>	Direct		

Created on: 16/12/2025