


28PV-16031603-1: Double Backplate elbow female, build in 16x3/8" x 16x3/8"



Commercial information

Basic unit dimensions

Height	37 mm
Length	120 mm
Width	69 mm
Net weight	0.329 kg

Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

System specific	✓	Outer pipe diameter connection	16 Millimetre
Housing material	Brass	Distance centre-to-centre	120 Millimetre
Surface protection	Untreated	Max. operating pressure at 20 °C	16 Bar
Connection	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Contour code	TH		
With connection indicator	✗		
With protective cap	✗		
With soundproofing set	✗		
With thermal insulation	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
Compliant with NF 545	✗		
KOMO certified	✓		