



Features


- DELTAWING 1200 4K SSC is a ceiling and wall surface, suspended LED luminaire with opal diffuser, 1160x160x60mm dimensions, 36W system power, 4,600lm flux and 128lm/W efficacy, CRI (Ra) >80, 4000K (Neutral White) CCT, chromaticity tolerance of 3-step MacAdam ellipse, Sylsmart Standalone enabled, RAL9003 finishing, L70B50 100khrs / L80B50 80khrs lifespan, IK06 impact resistance, IP44 ingress protection rating (in ceiling surface installation), Electrical protection Class I, Glow wire test 850°C.

Product Overview


Product name	DELTAWING 1200 4K SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	PC Polycarbonate, Steel
Mount	Ceiling surface mounting, Wall surface mounted
Fixture luminous flux (lm)	4600
Luminaire efficacy (lm/W)	128
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	36
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	RAL9003
IP rating	IP44
IK rating	IK06
Product EAN number	5410288429380
Warranty	5 years

Light your world

Photometry



Technical drawings



Light your world