


28PV-16041604-1: Double Backplate elbow female, build in 16x1/2" x 16x1/2"



Commercial information

Basic unit dimensions

| | |
|------------|----------|
| Height | 37 mm |
| Length | 150 mm |
| Width | 69 mm |
| Net weight | 0.355 kg |

Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

| | | | |
|-----------------------------|--------------|----------------------------------|------------------------|
| System specific | ✓ | Outer pipe diameter connection | 16 Millimetre |
| Housing material | Brass | Distance centre-to-centre | 153 Millimetre |
| Surface protection | Untreated | Max. operating pressure at 20 °C | 16 Bar |
| Connection | Press sleeve | Medium temperature (continuous) | -10 70 Degrees celsius |
| Contour code | TH | | |
| With connection indicator | ✗ | | |
| With protective cap | ✗ | | |
| DVGW quality mark for gas | ✗ | | |
| DVGW quality mark for water | ✓ | | |
| Compliant with NF 545 | ✗ | | |
| KOMO certified | ✓ | | |