

**QQPX8.E317914****Power Supplies for Use in Hazardous Locations Certified for Canada - Component**[Page Bottom](#)**Power Supplies for Use in Hazardous Locations Certified for Canada - Component**[See General Information for Power Supplies for Use in Hazardous Locations Certified for Canada - Component](#)**ABB STOTZ-KONTAKT GMBH**

E317914

HAUPTSTRASSE 14-16

78132 HORNBERG, GERMANY

Class 2 power supplies, Model(s) CP-E12/1.5, CP-E15/1.2, CP-E24/0.75, CP-E5/3.0**Class I, Division 2, Groups A, B, C and D**, Model(s) CP-E 12/10.0, CP-E 24/10.0, CP-E 24/20.0, CP-E 24/5.0, CP-E 48/10.0, CP-E 48/5.0, CP-T 24/10.0, CP-T 24/20.0, CP-T 24/40.0, CP-T 24/5.0, CP-T 48/10.0, CP-T 48/20.0, CP-T 48/5.0**Class I, Division 2, Groups A, B, C and D (switching)**, Model(s) CP-E12/2, CP-E12/5.0, CP-E24/1.25, CP-E24/2.5, CP-E48/0.62, CP-E48/1.25, CP-E5/6.0

Marking: Company name, model designation and Recognized Component Mark for Canada, .

[Last Updated](#) on 2009-10-26[Questions?](#)[Notice of Disclaimer](#)[Page Top](#)

Copyright © 2009 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.





QQGQ8.E196145

Power Supplies, Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component

Page Bottom

Power Supplies, Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component

See General Information for Power Supplies, Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component

ABB STOTZ-KONTAKT GMBH

E196145

HAUPTSTRASSE 14-16

78132 HORNBERG, GERMANY

Model No.	Rated Input		SC	Max Output			OC	SP	EP	FC	GC
	Volts	Hz		V	A	VA					
CP-A CM[*r]	13 - 30dc	-	3	30dc	0.1	3	3	60950-1	20B	0	0
CP-A RU	10-40dc	-	3	39.4dc	40	157.6	3	60950-1	20B	0	0
CP-C 24/10.0[*r]											
	110-240ac	48-63	0	24dc	10	240	3	60950-1	-	0	1
CP-C 24/20.0[*r]											
	110-240ac	48-63	0	24dc	20	480	-	60950-1	20B	0	1
CP-C 24/5.0											
	110-240ac	48-63	0	28	12	225	3	60950-1	-	0	1
CP-D 12/0.83											
	100-240ac	47-63	0	12.07	1.31	13.44	3	60950-1	20B	0	2
CP-D 12/2.1[*r]											
	100-240ac	47-63	0	12	2.1	-	-	60950-1	20B	0	2
CP-D 12/4.5											
	100-240ac	47-63	0	12.05dc	6	53.4	3	60950-1	20B	0	2
CP-D 12/6.0											
	100-240ac	47-63	0	12.02	9.11	90.1	3	60950-1	20B	0	2
CP-D 15/0.67											
	100-240ac	47-63	0	14.94	1.25	14.24	3	60950-1	20B	0	2
CP-D 15/2.0											
	100-240ac	47-63	0	15.1dc	3.67	38.05	3	60950-1	20B	0	2
CP-D 15/4.0											
	100-240ac	47-63	0	15.01dc	5.6	64.87	3	60950-1	20B	0	2
CP-D 15/5.0											
	100-240ac	47-63	0	15.023	8.76	98.2	3	60950-1	20B	0	2
CP-D 24/0.42											
	100-240ac	47-63	0	23.94	0.8	15.8	3	60950-1	20B	0	2
CP-D 24/1.3											
	100-240ac	47-63	0	24.08dc	3.1	37.52	3	60950-1	20B	0	2
CP-D 24/2.5											
	100-240ac	47-63	0	24.02dc	3.88	72.22	3	60950-1	20B	0	2
CP-D 24/3.8											

	100-240ac	47-63	0	24	3.8	91	3	60950-1	20B	0	2
CP-D 24/4.2											
	100-240ac	47-63	0	24.08	7.71	122.58	3	60950-1	20B	0	2
CP-D 5/1.5											
	100-240ac	47-63	0	4.99	2.54	10.36	3	60950-1	20B	0	2
CP-D 5/12.0											
	100-240ac	47-63	0	5.035	17.2	52.64	3	60950-1	20B	0	2
CP-D 5/3.0											
	100-240ac	47-63	0	5.038dc	7	21.8	3	60950-1	20B	0	2
CP-D 5/7.0											
	100-240ac	47-63	0	5.02dc	9.9	35.43	3	60950-1	20B	0	2
CP-E 5/3.0, CP-E 12/1.5, CP-E 15/1.2, CP-E 24/0.75											
	-	-	-	-	-	-	-	-	-	-	-
CP-E 12/10.0											
	115/ 220/ 230ac	47-63	0	12.02	14	124.68	3	60950-1	20B	0	1
CP-E 12/2.5											
	100-240ac	47-63	0	14.96dc	4	45.88	3	60950-1	20B	0	1
CP-E 12/5.0											
	100-240ac	47-63	0	14.76dc	7	87	3	60950-1	20B	0	1
CP-E 24/1.25											
	120-240ac	47-63	0	24dc	-	30	3	60950-1	20B	0	1
CP-E 24/10.0											
	115/ 230ac	47-63	0	24dc	14.5	308.1	3	60950-1	20B	0	1
CP-E 24/2.5											
	100-240ac	47-63	0	28.5dc	3.48	91.45	3	60950-1	20B	0	1
CP-E 24/20.0											
	115/ 230ac	47-63	0	24.07dc	27.3	567.1	3	60950-1	20B	0	0
CP-E 24/5.0											
	115/ 220/ 230ac	47-63	0	24.07	7.6	131.7	3	60950-1	20B	0	1
CP-E 48/0.62											
	100-240ac	47-63	0	56.87dc	0.93	42	3	60950-1	20B	0	1
CP-E 48/1.25											
	100-240ac	47-63	0	28.5dc	3.48	91.45	3	60950-1	20B	0	1
CP-E 48/10.0											
	115/ 230ac	47-63	0	48.05dc	13.5	583.9	3	60950-1	20B	0	0
CP-E 48/5.0[*r]											
	115/ 230ac	47-63	0	48dc	5	240	3	60950-1	20B	0	1
CP-E 5/6.0											
	100-240ac	47-63	0	5.87dc	7.9	41.38	3	60950-1	20B	0	1
CP-S 24/10.0[*r]											
	110-120/ 220-240ac	48-63	0	24dc	10	240	3	60950-1	-	0	1
CP-S 24/20.0[*r]											

	110-240ac	48-63	0	24dc	20	480	-	60950-1	20B	0	1
CP-S 24/5.0											
	110-240ac	48-63	0	24	12.5	176	3	60950-1	-	0	1
CP-T 24/10.0											
	3PH 400-500Vac	47-63	0	24.1dc	13.7	289.92	3	60950-1	20B	0	1
CP-T 24/20.0											
	3PH 400-500ac	47-63	0	24.1	29.6	513	3	60950-1	20B	0	1
CP-T 24/40.0											
	3PH 400-500Vac	47-63	0	24.1dc	44.5	1038	3	60950-1	20B	0	1
CP-T 24/5.0											
	3PH 400-500Vac	47-63	0	24.08dc	6.95	152.32	-	60950-1	20B	0	1
CP-T 48/10.0											
	3PH 400-500ac	47-63	0	48.2	19.7	498	3	60950-1	20B	0	1
CP-T 48/20.0											
	3PH 400-500Vac	47-63	0	48.1dc	27.5	1176	3	60950-1	20B	0	1
CP-T 48/5.0											
	3PH 400-500Vac	47-63	0	48.03dc	6.32	279.93	3	60950-1	20B	0	1
Systron PS TSL 24V/20A											
	100-120/ 208-240/ 115/ 230ac	50/60	0	54	21.5	516	3	1950	-	0	1

[*r] - Output values are rated.

Marking: Company name or trademark  **ABB**, model designation and Recognized Component Mark for Canada,



Last Updated on 2009-10-05

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

